

ToLEDo Superia T5 ECG HE V3 4FT 2400LM 840

Code article 0029263

SYLVANIA




50,000 hours average rated lifetime Last 2.5 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp High switching cycles – 200,000X High lumen efficacy Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast Works only with compatible electronic ballasts Ideal for factories, parking lots, supermarkets, department stores, schools and offices

Atouts techniques

Dimensions (mm)

Photométrie



ToLEDo Superia T5 ECG HE V3 4FT 2400LM 840

Code article 0029263

SYLVANIA

Données générales

Nom du produit	ToLEDo Superia T5 ECG HE V3 4FT 2400LM 840
Technologie	LED
Puissance (nominale) (W)	17
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Opal
Built in presence detector	NONE
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Warranty	5 ans

Données optiques

Useful luminous flux (Φ_{use})	2400
Flux lumineux utile (nominal) (lm)	2400
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Maintien du flux à la fin de la durée de vie nominale (lm)	70

Caractéristiques électriques

Power consumption (W)	17
Wattage (W)	17
Actuel (A)	215
Primary Supply/Product voltage - min (V)	130.0
Primary Supply/Product voltage - max (V)	130.0
Ignition voltage (V)	100
Control gear required	Yes
Type d'appareillage	Electronic ballast
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	17.7
Inrush Duration (μ s)	51
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	54
Max. products per 20A C Breaker	67
Max. products per 10A B Breaker	56
Max. products per 13A B Breaker	73
Max. products per 16A B Breaker	90

Durée de vie

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Durée de vie moyenne (nominale) (h)	50000

Données physiques

Housing colour	White
IP rating	IP20
Longueur (mm)	1162
Nominal Product Diameter (mm)	17
Poids (kg)	0.14

ToLEDo Superia T5 ECG HE V3 4FT 2400LM 840

Code article 0029263

SYLVANIA

Emballage

Product EAN number	5410288292632
Longueur simple de l'emballage (cm)	116.0
Largeur simple de l'emballage (cm)	2.0
Packaging single depth (cm)	2.0
DUN14 (inner)	15410288292639
Units per outer package	10
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

Sécurité

Condition de fonctionnement optimal (° C)	-20-45
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Utilisation pour applications sèches uniquement	Yes
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	None