

ToLEDo Lynx F 2450LM 2G10 840 SL

Code article 0030226


SYLVANIA



LED replacement for compact fluorescent Lynx F lamps. 30,000 hours average rated life (L70 F50). 3 years warranty. Quick, simple and safe replacement without rewiring. Direct retrofit – easiest way to upgrade existing luminaires to LED technology. Suitable for magnetic ballast/CCG and direct mains 220-240V AC operation. Low energy consumption and no flickering. Compact and durable construction. Minimum and maximum operating temperature: -20°C to 45°C. Ideal for commercial and residential applications including offices, hotels, restaurants, warehouses, supermarkets, corridors, in addition to living rooms, kitchens and garages. Warning: ToLEDo Lynx F lamps are not suitable for operation with electronic ballast/ECG operation.

Atouts techniques

Dimensions (mm)



Photométrie

ToLEDo Lynx F 2450LM 2G10 840 SL

Code article 0030226

SYLVANIA

Données générales

Nom du produit	ToLEDo Lynx F 2450LM 2G10 840 SL
Technologie	LED
Lamp shape	U shape
Cap/Base	2G10
Lamp finish	Opal
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Numéro virtuel FI	4941331
Warranty	3 ans

Données optiques

Useful luminous flux (Φuse)	2450
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	130
Photobiological Risk Group	RG0

Caractéristiques électriques

Power consumption (W)	20
Wattage (W)	20
Equivalent watt (W)	36
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	230
Control gear required	No
Dimmable	No
Courant d'appel (A)	15
Inrush Duration (µs)	200
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz

Durée de vie

Lifespan L70 B50	30000
------------------	-------

Données physiques

IP rating	IP20
Longueur (mm)	222
Largeur (mm)	89
Nominal Product Height (mm)	23
Poids (kg)	0.175

Emballage

Product EAN number	5410288302263
Longueur simple de l'emballage (cm)	9.1
Largeur simple de l'emballage (cm)	2.6
Packaging single depth (cm)	24.0
DUN14 (inner)	15410288302260
Units per outer package	6
Packaging outer length / height (cm)	17.0
Packaging outer width (cm)	9.6
Packaging outer depth (cm)	25.0

Sécurité

Condition de fonctionnement optimal (° C)	-20-45
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Utilisation pour applications sèches uniquement	No
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Not suitable for household