



# OPTICLIP R 1250 840 1L WHT DALI

Code article 0034036

**SYLVANIA**

## Données générales

Nom du produit	OPTICLIP R 1250 840 1L WHT DALI
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	5°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	4700
Luminaire efficacy (lm/W)	142
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	75
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

## Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	33
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class II
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Minimum dimming level (%)	1
Drive current (mA)	900
Max. drive current (mA)	900
Drive current - Range (mA)	/ 900mA
Courant d'appel (A)	5.6
Inrush Duration (µs)	50
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	37
Max. products per 16A C Breaker	59
Max. products per 10A B Breaker	37
Max. products per 16A B Breaker	59
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.75
Connectable conductor cross section - Max (mm <sup>2</sup> )	2.5

# OPTICLIP R 1250 840 1L WHT DALI

Code article 0034036

**SYLVANIA**

## Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Finition réflecteur	Matt
Longueur (mm)	1245
Largeur (mm)	307.5
Nominal Product Height (mm)	14
Poids (kg)	3.0

## Emballage

Product EAN number	5410288340364
Longueur simple de l'emballage (cm)	137.0
Largeur simple de l'emballage (cm)	9.0
Packaging single depth (cm)	36.0
DUN14 (inner)	05410288340364
Units per outer package	1
Packaging outer length / height (cm)	137.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	36.0

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	5-25
Utilisation pour applications sèches uniquement	No