

TRIDONIC LC 45W 500–1400MA BDW SC PRE2 + CABLE

Code article 0034059

SYLVANIA

PROTM



Compact constant current LED driver – dimmable. Compatible with Optilcip Sylsmart Standalone (SSC) enabled luminaires.

Atouts techniques

Photométrie

Données générales

Nom du produit	TRIDONIC LC 45W 500–1400MA BDW SC PRE2 + CABLE
Technologie	Driver
Type d'accessoire	Electrical
Montage	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002710
Warranty	5 ans

Caractéristiques électriques

Emergency type	
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.98
Courant d'appel (A)	23
Inrush Duration (µs)	200
Max. products per 10A C Breaker	23
Max. products per 13A C Breaker	31
Max. products per 16A C Breaker	38
Max. products per 20A C Breaker	48
Max. products per 10A B Breaker	14
Max. products per 13A B Breaker	19
Max. products per 16A B Breaker	23
Max. products per 20A B Breaker	29

TRIDONIC LC 45W 500–1400MA BDW SC PRE2 + CABLE

Code article 0034059

SYLVANIA

Données physiques

IP rating	IP20
Longueur (mm)	150
Largeur (mm)	43
Nominal Product Height (mm)	30
Poids (kg)	0.5

Emballage

Product EAN number	5410288340593
Longueur simple de l'emballage (cm)	11.0
Largeur simple de l'emballage (cm)	55.0
Packaging single depth (cm)	55.0
DUN14 (inner)	15410288340590
Units per outer package	12
Packaging outer length / height (cm)	11.0
Packaging outer width (cm)	55.0
Packaging outer depth (cm)	55.0