

DIN Rail DALI Universal Control Module

Code article 0041612

SYLVANIA



The Digital Addressable Lighting Interface (DALI) Ballast Module is an ultra-compact DIN rail mounted unit with connections for a DALI Universe, configurable inputs/outputs and an M-BUS network. Using DALI, you can connect up to 64 luminaires through a single power and data connection whilst retaining individual control. This is complimented with four additional channels of configurable I/O. The DALI Ballast Module can be used in standalone mode where it can be set-up directly via the on-board keypad and display driven menu system and the intelligent DALI setup assistant without the need for a PC. As part of a wider networked solution, DALI Ballast Modules can be configured to operate as part of an EcoControls fully addressable lighting management system.

Atouts techniques

Photométrie

Données générales

Nom du produit	DIN Rail DALI Universal Control Module
Configuré sans PC	Yes
Technologie	Controls
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC000533

Caractéristiques électriques

Input	Switch/Sensor
Input protocol	MBUS

Données physiques

IP rating	IP20
Longueur (mm)	64
Largeur (mm)	104
Nominal Product Height (mm)	100
Poids (kg)	0.47

Emballage

Product EAN number	5410288416120
Longueur simple de l'emballage (cm)	16.0
Largeur simple de l'emballage (cm)	10.8
Packaging single depth (cm)	7.0
Units per outer package	1
Packaging outer length / height (cm)	16.0
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	7.0

DIN Rail DALI Universal Control Module

Code article 0041612

SYLVANIA

Sécurité

Condition de fonctionnement optimal (° C)

-10-35