

N-Light Emergency Monitor

Code article 0041774

SYLVANIA

LiFeSafe



N-Light Emergency Monitor is a DALI Emergency lighting test and monitoring system. Works with DALI monitoring capable SylSafe products. Controls two DALI subnets with maximum 128 luminaires. For larger systems multiple N-Light monitors can be networked together. Touch screen controlled. Comes with long life CR2032 battery to retain information during power failure. Ethernet port for commissioning and networking. Commissioned with N-Light software. Password protected Engineering Mode. Available in recessed and surface mounting versions. Power consumption: 4.14W

Atouts techniques

Photométrie

Données générales

Nom du produit	N-Light Emergency Monitor
Technologie	Electronic Device
Montage	Ceiling surface mounting
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC002924
Warranty	5 ans

Données physiques

IP rating	IP20
IK rating	IK03
Longueur (mm)	4
Largeur (mm)	100
Nominal Product Diameter (mm)	160
Poids (kg)	0.31

Caractéristiques électriques

Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Electrical protection	Class I
Drive current (mA)	18

N-Light Emergency Monitor

Code article 0041774

SYLVANIA

Emballage

Product EAN number	5410288417745
Longueur simple de l'emballage (cm)	30.5
Largeur simple de l'emballage (cm)	14.9
Packaging single depth (cm)	9.7
DUN14 (inner)	05410288417745
Units per outer package	9
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	34.8
Packaging outer depth (cm)	35.7