

OTAO LINEAR REF BLK 4PCS

Code article 0041807

SYLVANIA

PROTM



Reflector replacement modules for Otao Linear reflector versions, 3000K/4000K LED light source included, black finishing, 4 modules per pack.

Atouts techniques

Photométrie

Données générales

Nom du produit	OTAO LINEAR REF BLK 4PCS
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	5°C...+50°C
Virtual assistant compatibility	N/A
ETIM Class	EC002556
Warranty	5 ans

Données optiques

Couleur de lumière	Warm White or Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

OTAO LINEAR REF BLK 4PCS

Code article 0041807

SYLVANIA

Caractéristiques électriques

Emergency type	
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Electrical protection	Class III
Dimmable	No
Dimming method	N/A
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	100000

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Diffuser material	Other
Finition réflecteur	Not Applicable
Poids (kg)	0.25

Emballage

Product EAN number	5410288418070
Longueur simple de l'emballage (cm)	29.0
Largeur simple de l'emballage (cm)	5.0
Packaging single depth (cm)	13.0
DUN14 (inner)	15410288418077
Units per outer package	100
Packaging outer length / height (cm)	31.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	29.5

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	5-50