

ISOLINE 1690MM 4K ASYL DA 8C

Code article 0042527

SYLVANIA


PROTM




Isoline LED linear DALI dimmable luminaire for industrial and commercial applications. 1690 mm length with asymmetrical (Left) optics provide homogenous light distribution for wide, shelf areas. Suitable for DALI Dimming. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, 3 SDCM. 56 W power consumption, 8000 lm luminous flux, 143 lm/W efficacy, 1690 mm x 62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, DC 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.

Atouts techniques

Dimensions (mm)



Photométrie



ISOLINE 1690MM 4K ASYL DA 8C

Code article 0042527

SYLVANIA

Données générales

Nom du produit	ISOLINE 1690MM 4K ASYL DA 8C
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	0°C...+35°C
ETIM Class	EC000986
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	8000
Luminaire efficacy (lm/W)	143
Température de couleur (K)	4000
Colour Code	840
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	56
Primary Supply/Product voltage - min (V)	198.0
Primary Supply/Product voltage - max (V)	264.0
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	5.5
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Minimum dimming level (%)	1
Drive current (mA)	250
Courant d'appel (A)	28
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A B Breaker	14
Max. products per 16A B Breaker	23
Connectable conductor cross section - Min (mm²)	0.5
Connectable conductor cross section - Max (mm²)	4

Durée de vie

Lifespan L70 B50	60000
Lifespan L80 B10	60000
Lifespan L90 B10	31500

ISOLINE 1690MM 4K ASYL DA 8C

Code article 0042527



Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
IK rating of sensor	IK03
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Longueur (mm)	1690
Largeur (mm)	62
Nominal Product Height (mm)	59
Poids (kg)	3.5

Emballage

Product EAN number	5410288425276
Longueur simple de l'emballage (cm)	185.0
Largeur simple de l'emballage (cm)	7.2
Packaging single depth (cm)	6.9
DUN14 (inner)	05410288425276
Units per outer package	1
Packaging outer length / height (cm)	185.0
Packaging outer width (cm)	7.2
Packaging outer depth (cm)	6.9

Sécurité

Glow Wire Test (°C)	650
---------------------	-----