

RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE

Code article 0042585

SYLVANIA

PROTM



RTS LED linear luminaire for industrial and commercial applications. 1500 mm length with asymmetrical (Left) optics provide homogenous light distribution for wide, shelf areas. Steel housing, White color, -25 ... +30 °C operating temperature range, 4000 K, CRI 80, 3 SDMC. 50 W power consumption, 8000 lm luminous flux, 160 lm/W efficacy, 1500 mm x 70.2 mm x 78.6 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 120,000 hours.

Atouts techniques

Dimensions (mm)




L	600	900	1202	1500	2403	3000	3605	4500
---	-----	-----	------	------	------	------	------	------

Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Illuminance [lx]
0.5	0.96 1.06	43° 47°	1133 1267	2197 1665
1.0	1.92 2.11	43° 47°	2266 453	549 368
1.5	2.88 3.26	43° 47°	3399 244	233 144
2.0	3.84 4.35	43° 47°	4532 171	175 114
2.5	4.81 5.44	43° 47°	5665 131	137 86
3.0	5.77 6.52	43° 47°	6800 91	91 61

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 94.9°)
 — C90 - C270 (Half beam angle: 87.8°)



RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE

Code article 0042585

SYLVANIA

Données générales

Nom du produit	RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE
Technologie	LED
Cap/Base	N/A
Housing	Steel
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-25°C...+30°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000986
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	8000
Luminaire efficacy (lm/W)	160
Température de couleur (K)	4000
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Asymmetric
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	50
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	620
Courant d'appel (A)	20
Inrush Duration (µs)	250
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 16A C Breaker	27
Max. products per 16A B Breaker	19

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	75000

Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK03
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Longueur (mm)	1500
Largeur (mm)	70.2
Nominal Product Height (mm)	78.6
Poids (kg)	1.7

RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE

Code article 0042585

SYLVANIA

Emballage

Product EAN number	5410288425856
Longueur simple de l'emballage (cm)	150.0
Largeur simple de l'emballage (cm)	7.5
Packaging single depth (cm)	6.5
DUN14 (inner)	15410288425853
Units per outer package	10
Packaging outer length / height (cm)	157.0
Packaging outer width (cm)	44.0
Packaging outer depth (cm)	21.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-25-30