

PANEL IP66 CR R 623S MSG L3 5360LM 840

Code article 0042761

SYLVANIA


Atouts techniques

Photométrie

0.5	1.13 1.12	E(0°) E(C90) E(C270)	8902 1291 1211
1.0	2.27 2.24	E(0°) E(C90) E(C270)	2225 321 323
1.5	3.40 3.37	E(0°) E(C90) E(C270)	989 143 145
2.0	4.54 4.49	E(0°) E(C90) E(C270)	599 81 82
2.5	5.67 5.61	E(0°) E(C90) E(C270)	399 52 52
3.0	6.81 6.73	E(0°) E(C90) E(C270)	247 38 38

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 96.6°)
— C90 - C270 (Half beam angle: 97.2°)



Données générales

Nom du produit	PANEL IP66 CR R 623S MSG L3 5360LM 840
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+60°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	5360
Luminaire efficacy (lm/W)	145
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG0

PANEL IP66 CR R 623S MSG L3 5360LM 840

Code article 0042761

SYLVANIA

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	37
Primary Supply/Product voltage - min (V)	240.0
Primary Supply/Product voltage - max (V)	220.0
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class I
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	23
Inrush Duration (µs)	140
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	39
Max. products per 16A C Breaker	64
Max. products per 16A B Breaker	38
Connectable conductor cross section - Min (mm ²)	0.5
Connectable conductor cross section - Max (mm ²)	2.5

Durée de vie

Lifespan L70 B50 | 100000

Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP66
IK rating	IK08
Diffuser finish	Opal
Diffuser material	Safety tempered glass
Longueur (mm)	623
Largeur (mm)	623
Nominal Product Height (mm)	79
Poids (kg)	12.0

Emballage

Product EAN number	5410288427614
Longueur simple de l'emballage (cm)	65.0
Largeur simple de l'emballage (cm)	65.0
Packaging single depth (cm)	9.5
DUN14 (inner)	05410288427614
Units per outer package	1
Packaging outer length / height (cm)	65.0
Packaging outer width (cm)	65.0
Packaging outer depth (cm)	9.5

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-60