



AREUM SUSPENDED 1500 D/I 4000K SSC WHITE

Code article 0042977

SYLVANIA


PROTM



AREUM SUSPENDED 1500 D/I 4000K SSC WHITE is a highly efficient suspended LED luminaire with 70% direct and 30% indirect light distribution. Ultra thin (17mm) aluminium body with rounded edges. Length 1500mm, width 300mm. White RAL9016 powder coated luminaire body, powder coated steel surface gearbox and Y-shape power feeded suspension cables. SylSmart Standalone capable. Luminous flux: 7000lm, Power consumption: 57W. Luminaire efficacy: 123lm/W. CRi (Ra)>80 4000K (Neutral White) LED, chromaticity tolerance: SDCM<3. Lifespan: L80B10 57,000h. UGR<19, Luminance at 65°<3000 cd/m2. Photobiological safety risk group 0. Electrical protection: Class I. Glow Wire Test 650°C.

Atouts techniques

Dimensions (mm)




Photométrie

Distance [m]	Cone diameter [m]	E171	E180	E190	E200	E210	E220	E230	E240	E250	E260	E270	E280	E290	E300	ILLUMINANCE [lx]
0.5	0.84 1.00	507	507	507	507	507	507	507	507	507	507	507	507	507	507	9485
1.0	1.67 2.01	507	507	507	507	507	507	507	507	507	507	507	507	507	507	2386
1.5	2.51 3.01	507	507	507	507	507	507	507	507	507	507	507	507	507	507	1052
2.0	3.34 4.01	507	507	507	507	507	507	507	507	507	507	507	507	507	507	592
2.5	4.18 5.02	507	507	507	507	507	507	507	507	507	507	507	507	507	507	379
3.0	5.02 6.02	507	507	507	507	507	507	507	507	507	507	507	507	507	507	260

Distance [m] Cone diameter [m] ILLUMINANCE [lx]

— C0 - C180 (Half beam angle: 90°)
— C90 - C270 (Half beam angle: 78.8°)



AREUM SUSPENDED 1500 D/I 4000K SSC WHITE

Code article 0042977

SYLVANIA

Données générales

Nom du produit	AREUM SUSPENDED 1500 D/I 4000K SSC WHITE
Technologie	LED
Cap/Base	N/A
Housing	Aluminium, Steel
Montage	Suspended
Built in presence detector	NONE
General application	Office
Operating temperature range (°C)	5°C...+35°C
Virtual assistant compatibility	N/A
ETIM Class	EC001743
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	7000
Luminaire efficacy (lm/W)	125
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	84
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	56
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Standalone (SSC)
Minimum dimming level (%)	1
Drive current (mA)	1400
Courant d'appel (A)	21.7
Inrush Duration (µs)	306
Energy Efficiency Class (A->G) of contained light source	C, C(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	14
Max. products per 16A C Breaker	23
Max. products per 16A B Breaker	23
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	1.5

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B10	57000
Lifespan L90 B50	37000
Lifespan L90 B10	29000

AREUM SUSPENDED 1500 D/I 4000K SSC WHITE

Code article 0042977

SYLVANIA

Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
Diffuser finish	Diffuse
Diffuser material	PS Polystyrene
Finition réflecteur	Not Applicable
Longueur (mm)	1500
Largeur (mm)	300
Nominal Product Height (mm)	17
Poids (kg)	5.47

Emballage

Product EAN number	5410288429779
Longueur simple de l'emballage (cm)	155.0
Largeur simple de l'emballage (cm)	45.5
Packaging single depth (cm)	6.0
DUN14 (inner)	15410288429776
Units per outer package	4
Packaging outer length / height (cm)	156.5
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	26.5

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	5-35