

# SYLPROOF LED 37W 1565MM S 4000K

Code article 0047884

**SYLVANIA**



**UK  
CA**



Sylproof LED, Polycarbonate housing, Polycarbonate Diffuser, 37W, 3794lumen, 4000K Neutral White, Non Dimmable Electronic Driver, Push in connector, IP65, IK08, (LxWxD) 1565x83x91mm

## Atouts techniques


### Dimensions (mm)

	L	I	H	F
Single	662	83	91	390
Twin	662	123	91	390
Single	1265	83	91	855
Twin	1265	123	91	855
Single	1565	83	91	955
Twin	1565	123	91	955

### Photométrie

Distance [m]	Core diameter [m]	Illuminance [lx]
0.5	2.88 1.07	4917 E10° 98.8° 105 E100° 27.0° 89
1.0	5.16 2.14	1079 E10° 98.8° 28 E100° 27.0° 171
1.5	7.73 3.22	480 E10° 98.8° 12 E100° 27.0° 77
2.0	10.31 4.29	270 E10° 98.8° 6 E100° 27.0° 41
2.5	12.89 5.36	173 E10° 98.8° 4 E100° 27.0° 28
3.0	15.47 6.43	100 E10° 98.8° 3 E100° 27.0° 18

Distance [m]    Core diameter [m]    Illuminance [lx]  
 — C0 - C180 (Half beam angle: 94.0°)  
 — C90 - C270 (Half beam angle: 137.0°)



# SYLPROOF LED 37W 1565MM S 4000K

Code article 0047884

**SYLVANIA**

## Données générales

Nom du produit	SYLPROOF LED 37W 1565MM S 4000K
Technologie	LED
Housing	PC Polycarbonate
Montage	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Under Canopy
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+30°C
ETIM Class	EC000109
Numéro virtuel FI	4323249
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	3794
Luminaire efficacy (lm/W)	101
LOR (%)	100
Température de couleur (K)	4000
IRC (Ra)	80
Colour Consistency (SDCM)	6
Chromaticité réglable	N
Distribution type	Direct
Glare control	< 19
Photobiological Risk Group	RG0

## Caractéristiques électriques

Consommation électrique totale (W)	37.3
Electrical protection	Class I
Type d'appareillage	Electronic ballast
Montage de l'appareillage	Integral
Dimming method	N/A
Drive current (mA)	550
Max. products per 10A C Breaker	30
Max. products per 16A C Breaker	51
Max. products per 20A C Breaker	62
Max. products per 10A B Breaker	28
Max. products per 16A B Breaker	45
Max. products per 20A B Breaker	57

## Données physiques

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Finition réflecteur	Other
Longueur (mm)	1565
Largeur (mm)	83
Nominal Product Height (mm)	91
Poids (kg)	1.778

## Emballage

Product EAN number	5410288478845
Longueur simple de l'emballage (cm)	157.0
Largeur simple de l'emballage (cm)	8.6
Packaging single depth (cm)	9.6
DUN14 (inner)	15410288478842
Units per outer package	1
Packaging outer length / height (cm)	157.0
Packaging outer width (cm)	8.6
Packaging outer depth (cm)	9.6

# SYLPROOF LED 37W 1565MM S 4000K

Code article 0047884

**SYLVANIA**

## Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-30-30
Variateurs compatibles	Non-dim / not dimmable (switched only)