


START eco Bollard L-Shape M IP65 620lm 830 BLK

Code article 0047951


SYLVANIA



Exterior integrated LED bollard, Decorative bollard with a sleek design, Metal - Aluminium housing - RAL9005, 620LM, 8W, 78lm/W, 3000K, Electronic driver, Driver Current: 60mA, CRI80, IP65, IK05, 30,000hrs (L70), (HxWxD) 500x160x90mm, 5 step MacAdam ellipse, 1.53 kg, RAL 9005, Class 1, 220-240V, energy class: A++, A+, A

Atouts techniques

Dimensions (mm)




Photométrie

0.5	1.22 1.13	1110 E17 E150 50° E100 45°	142 100
1.0	2.44 2.25	270 E17 E150 50° E100 45°	70 50 41
1.5	3.67 3.38	134 E17 E150 50° E100 45°	46 34 25
2.0	4.88 4.51	70 E17 E150 50° E100 45°	25 18 13
2.5	6.11 5.63	46 E17 E150 50° E100 45°	15 11 8
3.0	7.33 6.76	31 E17 E150 50° E100 45°	9 6 4

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 90.9°)
— C90 - C270 (Half beam angle: 101.4°)



START eco Bollard L-Shape M IP65 620lm 830 BLK

Code article 0047951

SYLVANIA

Données générales

Nom du produit	START eco Bollard L-Shape M IP65 620lm 830 BLK
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000301
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	620
Luminaire efficacy (lm/W)	78
Température de couleur (K)	3000
Colour Code	830
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	92
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	8
Actuel (A)	0.064
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.57
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	120.0
Electrical protection	Class I
Dimmable	No
Drive current (mA)	60
Courant d'appel (A)	10
Inrush Duration (µs)	250
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	60
Max. products per 13A C Breaker	80
Max. products per 16A C Breaker	100
Max. products per 20A C Breaker	120

Durée de vie

Lifespan L70 B50 | 30000

Données physiques

Housing colour	RAL 9005 - Jet black
IP rating	IP65
IK rating	IK05
Diffuser finish	Transparent
Diffuser material	Glass
Longueur (mm)	90
Largeur (mm)	160
Nominal Product Height (mm)	500
Poids (kg)	1.52

START eco Bollard L-Shape M IP65 620lm 830 BLK

Code article 0047951

SYLVANIA

Emballage

Product EAN number	5410288479514
Longueur simple de l'emballage (cm)	53.5
Largeur simple de l'emballage (cm)	19.5
Packaging single depth (cm)	12.5
DUN14 (inner)	15410288479511
Units per outer package	3
Packaging outer length / height (cm)	21.5
Packaging outer width (cm)	55.5
Packaging outer depth (cm)	39.5

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-45