


START eco Flood Flat IP65 900lm 840

Code article 0047961


SYLVANIA



The new Start eco Flood Flat comes with improved design. The streamlined, durable, lightweight die-cast aluminium body makes it a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black die-cast aluminum housing, white reflector, 950 lm, 10 W, 95 lm/W, 4000K, drive current 38.6 mA, non dimmable, CRI>80, IP65, IK06, Class I, lumen maintenance L70:B50: 30000 hrs, 114 x 96 x 38 mm (L x W x H). Weight: 0.33kg. Energy class: A++ A+ A.


Atouts techniques

Dimensions (mm)



Photométrie

Distance (m)	Cone diameter (m)	Beam angle (°)	Beam diameter (m)	Illuminance (lx)
0.5	1.44	50.2°	1.44	1489
1.0	2.88	50.2°	2.88	367
1.5	4.32	50.2°	4.32	163
2.0	5.76	50.2°	5.76	92
2.5	7.19	50.2°	7.19	59
3.0	8.63	50.2°	8.63	41



START eco Flood Flat IP65 900lm 840

Code article 0047961

SYLVANIA

Données générales

Nom du produit	START eco Flood Flat IP65 900lm 840
Technologie	LED
Housing	Aluminium
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Numéro virtuel FI	4579433
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	950
Luminaire efficacy (lm/W)	95
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Beam Angle (°)	110
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	10
Lamp power factor	0.85
Electrical protection	Class I
Drive current (mA)	38.6
Courant d'appel (A)	7
Inrush Duration (µs)	400
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	57
Max. products per 13A C Breaker	74
Max. products per 16A C Breaker	91
Max. products per 20A C Breaker	114
Max. products per 10A B Breaker	28
Max. products per 13A B Breaker	37
Max. products per 16A B Breaker	46
Max. products per 20A B Breaker	57
Mains surge immunity (differential mode -> L-N) (kV)	1
Mains surge immunity (common mode -> L/N - GND) (kV)	2

Durée de vie

Lifespan L70 B50	30000
------------------	-------

Données physiques

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK06
Longueur (mm)	114
Largeur (mm)	96
Nominal Product Height (mm)	38
Poids (kg)	0.33
Wind Area (m²)	0.008

START eco Flood Flat IP65 900lm 840

Code article 0047961



Emballage

Product EAN number	5410288479613
Longueur simple de l'emballage (cm)	11.9
Largeur simple de l'emballage (cm)	5.7
Packaging single depth (cm)	14.6
DUN14 (inner)	15410288479610
Units per outer package	12
Packaging outer length / height (cm)	37.8
Packaging outer width (cm)	25.0
Packaging outer depth (cm)	17.9

Sécurité

Condition de fonctionnement optimal (° C)	-20-40
---	--------