

Start Batten 1500 7000lm DALI 830/840

Code article 0048984

SYLVANIA

Données générales

Nom du produit	Start Batten 1500 7000lm DALI 830/840
Technologie	LED
Cap/Base	N/A
Housing	Steel
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC000109
Numéro virtuel FI	4279489
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	7100
Luminaire efficacy (lm/W)	138
Couleur de lumière	Warm White or Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	145x110
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	51.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	Yes
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	350
Courant d'appel (A)	38.2
Inrush Duration (µs)	289
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	9
Max. products per 20A C Breaker	11
Max. products per 10A B Breaker	4
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	7
Connectable conductor cross section - Max (mm²)	1.5

Durée de vie

Lifespan L70 B50	120000
Lifespan L80 B50	120000

Start Batten 1500 7000lm DALI 830/840

Code article 0048984



Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Longueur (mm)	1500
Largeur (mm)	64
Nominal Product Height (mm)	65
Poids (kg)	1.556

Emballage

Product EAN number	5410288489841
Longueur simple de l'emballage (cm)	151.1
Largeur simple de l'emballage (cm)	6.7
Packaging single depth (cm)	6.7
DUN14 (inner)	15410288489848
Units per outer package	6
Packaging outer length / height (cm)	152.5
Packaging outer width (cm)	15.3
Packaging outer depth (cm)	22.3

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40