

Start Flood Flat IP65 10000LM 840 Black

Code article 0050126


SYLVANIA



The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 10000 lm, 73 W, 137 lm/W, 4000K, non dimmable, CRI>80, IP65, IK07, Class I, lifespan L70:B50: 90000 hrs, 195 x 250 x 33 mm (L x W x H). Weight: 1.19kg.


Atouts techniques

Dimensions (mm)



Photométrie

Distance (m)	Cone diameter (m)	Beam angle (°)	Beam diameter (m)	Illuminance (lx)
0.5	1.55	114.27	1.55	14280
1.0	3.09	114.27	3.09	3587
1.5	4.64	114.27	4.64	1535
2.0	6.18	114.27	6.18	892
2.5	7.73	114.27	7.73	571
3.0	9.27	114.27	9.27	396



Start Flood Flat IP65 10000LM 840 Black

Code article 0050126

SYLVANIA

Données générales

Nom du produit	Start Flood Flat IP65 10000LM 840 Black
Technologie	LED
Cap/Base	N/A
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	10000
Luminaire efficacy (lm/W)	137
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	110
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	73
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Drive current (mA)	330
Courant d'appel (A)	22.4
Inrush Duration (µs)	600
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	14
Max. products per 13A C Breaker	18
Max. products per 16A C Breaker	23
Max. products per 20A C Breaker	28
Max. products per 10A B Breaker	8
Max. products per 13A B Breaker	11
Max. products per 16A B Breaker	13
Max. products per 20A B Breaker	17

Durée de vie

Lifespan L70 B50	90000
Lifespan L80 B50	89000
Lifespan L80 B20	57000

Start Flood Flat IP65 10000LM 840 Black

Code article 0050126



Données physiques

Housing colour	Black
IP rating	IP65
IK rating	IK07
Longueur (mm)	195
Largeur (mm)	250
Nominal Product Height (mm)	33
Poids (kg)	1.19

Emballage

Product EAN number	5410288501260
Longueur simple de l'emballage (cm)	26.0
Largeur simple de l'emballage (cm)	5.0
Packaging single depth (cm)	22.5
DUN14 (inner)	15410288501267
Units per outer package	6
Packaging outer length / height (cm)	53.5
Packaging outer width (cm)	17.0
Packaging outer depth (cm)	24.5

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40