

LED PIPE G2 L600 HIGH OUTPUT NW

Code article 0051047

SYLVANIA



LED T5 replacement batten, high output range: more lumens per meter with efficiency up to 125 lum/watt, seamless linking (up to 10M), Ideal for direct lighting such as under cabinet or in kitchens, 150 degree beam angle, includes switch, includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets


Atouts techniques

Dimensions (mm)



L	H	W
300	35	24
600	35	24
900	35	24
1200	35	24
1500	35	24

Photométrie



Données générales

Nom du produit	LED PIPE G2 L600 HIGH OUTPUT NW
Technologie	LED
Housing	PC Polycarbonate
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
Numéro virtuel SE	7505154
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	1050
Luminaire efficacy (lm/W)	116
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0

LED PIPE G2 L600 HIGH OUTPUT NW

Code article 0051047

SYLVANIA

Caractéristiques électriques

Consommation électrique totale (W)	9
Lamp power factor	0.9
Electrical protection	Class II
Dimmable	No
Drive current (mA)	125
Courant d'appel (A)	2
Inrush Duration (µs)	50
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	16
Max. products per 13A C Breaker	21
Max. products per 16A C Breaker	25
Max. products per 20A C Breaker	25
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	13
Max. products per 16A B Breaker	16
Max. products per 20A B Breaker	20

Durée de vie

Lifespan L70 B50 | 30000

Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK02
Diffuser material	PC Polycarbonate
Longueur (mm)	600
Largeur (mm)	24
Nominal Product Height (mm)	35
Poids (kg)	0.188

Emballage

Product EAN number	5410288510477
Longueur simple de l'emballage (cm)	4.1
Largeur simple de l'emballage (cm)	3.2
Packaging single depth (cm)	72.0
DUN14 (inner)	15410288510474
Units per outer package	20
Packaging outer length / height (cm)	74.0
Packaging outer width (cm)	18.5
Packaging outer depth (cm)	19.0

Sécurité

Condition de fonctionnement optimal (° C) | -20-40