

Kalani IP66 14KLM 840 ASYM DALI

Code article 0056821

SYLVANIA


PROTM




Exterior LED Floodlight, comes complete with 1000mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, integrated anti-condensation valve, IP66, IK08, Class I, 4000K, CRI80, DALI dimmable, 15600lm, 102W, 153lm/W, Asymmetrical Wide beam, 100.000hrs L80B50 lifespan, 405 x 320 x 73mm (LxWxD) dimensions, 4.3kg weight, RAL9017 Traffic Black color, Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3, Resistance against swimming pool atmospheric environments.

Atouts techniques

Dimensions (mm)



Photométrie



Kalani IP66 14KLM 840 ASYM DALI

Code article 0056821

SYLVANIA

Données générales

Nom du produit	Kalani IP66 14KLM 840 ASYM DALI
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Other
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Numéro virtuel FI	4579657
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	15600
Luminaire efficacy (lm/W)	153
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	65x120
Distribution type	Asymmetric
Photobiological Risk Group	RG1

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	102
Actuel (A)	0.443
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	Yes
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	480
Courant d'appel (A)	86
Inrush Duration (µs)	256
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	12
Max. products per 13A C Breaker	13
Max. products per 16A C Breaker	17
Max. products per 20A C Breaker	22
Max. products per 10A B Breaker	8
Max. products per 13A B Breaker	9
Max. products per 16A B Breaker	12
Max. products per 20A B Breaker	15
Mains surge immunity (differential mode -> L-N) (kV)	10
Mains surge immunity (common mode -> L/N - GND) (kV)	10
Connectable conductor cross section - Min (mm²)	1
Connectable conductor cross section - Max (mm²)	1

Kalani IP66 14KLM 840 ASYM DALI

Code article 0056821

SYLVANIA

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L80 B20	93000

Données physiques

Housing colour	RAL 9017 - Traffic black
IP rating	IP66
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	Glass
Finition réflecteur	Matt
Longueur (mm)	405
Largeur (mm)	320
Nominal Product Height (mm)	73
Poids (kg)	4.3

Emballage

Product EAN number	5410288568218
Longueur simple de l'emballage (cm)	40.4
Largeur simple de l'emballage (cm)	31.7
Packaging single depth (cm)	7.3
DUN14 (inner)	05410288568218
Units per outer package	1
Packaging outer length / height (cm)	40.4
Packaging outer width (cm)	31.7
Packaging outer depth (cm)	7.3

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-30-50