

START Waterproof Single 1200 IP65 2800lm 865

Code article 0067963


SYLVANIA



Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 2750 lm, 22 W, 125 lm/W, 6500 K, drive current 350 mA, non dimmable, CRI80, IP65, IK08, Class I, nominal average lifetime (h): 50000, 1278 mm x 84 mm x 75 mm, energy class: A++ A+ A, D-mark


Atouts techniques

Dimensions (mm)



Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Illuminance [lx]
0.5	1.40 1.25	54° 54°	1.40 1.25	2750 3599
1.0	2.80 2.51	54° 54°	2.80 2.51	688 1439
1.5	4.21 3.76	54° 54°	4.21 3.76	305 615
2.0	5.61 5.01	54° 54°	5.61 5.01	153 308
2.5	7.01 6.26	54° 54°	7.01 6.26	95 185
3.0	8.41 7.52	54° 54°	8.41 7.52	63 125



START Waterproof Single 1200 IP65 2800lm 865

Code article 0067963

SYLVANIA

Données générales

Nom du produit	START Waterproof Single 1200 IP65 2800lm 865
Technologie	LED
Housing	PC Polycarbonate
Montage	Ceiling surface mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	2750
Luminaire efficacy (lm/W)	125
Température de couleur (K)	6500
Couleur de lumière	Daylight
IRC (Ra)	80
Glare control	< 26
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	22
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	60
Max. products per 13A C Breaker	79
Max. products per 16A C Breaker	97
Max. products per 20A C Breaker	121
Max. products per 10A B Breaker	60
Max. products per 13A B Breaker	79
Max. products per 16A B Breaker	97
Max. products per 20A B Breaker	121

Durée de vie

Lifespan L80 B10	60000
Lifespan L90 B50	59000
Lifespan L90 B20	53000
Lifespan L90 B10	50000

START Waterproof Single 1200 IP65 2800lm 865

Code article 0067963



Données physiques

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Longueur (mm)	1278
Largeur (mm)	84
Nominal Product Height (mm)	75
Poids (kg)	1.61

Emballage

Product EAN number	5410288679631
Longueur simple de l'emballage (cm)	137.2
Largeur simple de l'emballage (cm)	8.8
Packaging single depth (cm)	8.4
DUN14 (inner)	05410288679631
Units per outer package	1
Packaging outer length / height (cm)	137.2
Packaging outer width (cm)	8.8
Packaging outer depth (cm)	8.4

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-40
Utilisation pour applications sèches uniquement	No