

SYLPROOF TOLEDO T8 L1500 HOUSING SINGLE

Code article 0090082

SYLVANIA

YourHome™



Weatherproof empty housing compatible with ToLEDo T8 LED tubes. Easy to install with stainless steel fixing brackets for ceiling mounting. Polycarbonate housing and diffuser. IP65; IK08; 1580mm x 60mm x 65mm

Atouts techniques

Photométrie

Données générales

Nom du produit	SYLPROOF TOLEDO T8 L1500 HOUSING SINGLE
Technologie	LED
Cap/Base	G13
Housing	PC Polycarbonate
Montage	Wall surface mounted
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	1
Luminaire efficacy (lm/W)	1
Couleur de lumière	N/A
Colour Variation Initial (SDCM)	N/A
Distribution type	Symmetric
Photobiological Risk Group	Not applicable

SYLPROOF TOLEDO T8 L1500 HOUSING SINGLE

Code article 0090082

SYLVANIA

Caractéristiques électriques

Lampe incluse	Fixture without Lightsource
Emergency type	
Consommation électrique totale (W)	0.1
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	15
Electrical protection	Class II
Type d'appareillage	Not required
Dimmable	No
Dimming method	N/A
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	1
Max. products per 16A C Breaker	1
Max. products per 16A B Breaker	1
Connectable conductor cross section - Max (mm ²)	1.5

Durée de vie

Lifespan L70 B50	25000
Lifespan L80 B10	25000
Lifespan L90 B10	25000

Données physiques

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Longueur (mm)	1580
Largeur (mm)	65
Nominal Product Height (mm)	60
Poids (kg)	0.75

Emballage

Product EAN number	5410288900827
Longueur simple de l'emballage (cm)	163.5
Largeur simple de l'emballage (cm)	6.4
Packaging single depth (cm)	4.5
DUN14 (inner)	15410288900824
Units per outer package	12
Packaging outer length / height (cm)	165.0
Packaging outer width (cm)	16.0
Packaging outer depth (cm)	29.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40