

SylSpot Neos 400lm 830 IP65 10-PACK

Code article 0090088

SYLVANIA

Données générales

Nom du produit	SylSpot Neos 400lm 830 IP65 10-PACK
Technologie	LED
Cap/Base	N/A
Housing	Polymer
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Residential & Consumer
Operating temperature range (°C)	-10°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	400
Luminaire efficacy (lm/W)	93
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Distribution type	Symmetric
Photobiological Risk Group	RG1

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	4.8
Actuel (A)	0.02
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.5
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	150
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	15
Inrush Duration (µs)	400
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	91
Max. products per 16A C Breaker	147
Max. products per 16A B Breaker	87
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	1.5

Durée de vie

Lifespan L70 B50	15000
Lifespan L80 B10	10000

SylSpot Neos 400lm 830 IP65 10-PACK

Code article 0090088



Données physiques

Housing colour	White
IP rating	IP65/20
IK rating	IK03
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Finition réflecteur	Not Applicable
Nominal Product Height (mm)	35
Nominal Product Diameter (mm)	87
Poids (kg)	0.55

Emballage

Product EAN number	5410288900889
Longueur simple de l'emballage (cm)	29.2
Largeur simple de l'emballage (cm)	10.6
Packaging single depth (cm)	17.1
DUN14 (inner)	15410288900886
DUN14 (outer)	25410288900883
Units per outer package	4
Packaging outer length / height (cm)	50.0
Packaging outer width (cm)	20.6
Packaging outer depth (cm)	24.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-10-40