

SYLCIRCLE IP54 2500/4000LM 830/840 DT

Code article 0090122

SYLVANIA

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	33
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Drive current (mA)	176
Courant d'appel (A)	18
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	31
Max. products per 13A C Breaker	40
Max. products per 16A C Breaker	50
Max. products per 20A C Breaker	62
Max. products per 10A B Breaker	19
Max. products per 13A B Breaker	24
Max. products per 16A B Breaker	30
Max. products per 20A B Breaker	37
Connectable conductor cross section - Max (mm²)	1.5

Durée de vie

Lifespan L70 B50	120000
Lifespan L70 B20	120000
Lifespan L70 B10	120000
Lifespan L80 B50	105000
Lifespan L80 B20	95000
Lifespan L80 B10	89000
Lifespan L90 B50	51000
Lifespan L90 B20	47000
Lifespan L90 B10	44000

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP54
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PMMA Acrylic
Nominal Product Height (mm)	105
Nominal Product Diameter (mm)	400
Poids (kg)	1.09

Emballage

Product EAN number	5410288901220
Longueur simple de l'emballage (cm)	43.0
Largeur simple de l'emballage (cm)	43.0
Packaging single depth (cm)	11.5
DUN14 (inner)	15410288901227
Units per outer package	5
Packaging outer length / height (cm)	60.0
Packaging outer width (cm)	44.3
Packaging outer depth (cm)	44.8

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-40

SYLCIRCLE IP54 2500/4000LM 830/840 DT

Code article 0090122

SYLVANIA