

MYRIAD ADJ ROUND WHITE 3000K PHDIM WHITE BEZ

Code article 2056208

Concord



The Myriad Adjustable Round recessed spotlight is a high efficient accent downlight, fixture color RAL 9016 - Traffic white / Bezel, correlated colour temperature of 3000K, color rendering index Ra85, fixture lumen 702lm, total power consumption 10W, luminaire efficacy 70 lm/W, nominal light beam angle 24°, mains voltage 230-240V~ AC, control technology type: leading edge/trailing edge phase dim, product length 76mm, width 76mm, height 115mm, cut-out dimension 76mm, IP rating IP20, 5 years warranty.

Atouts techniques

Dimensions (mm)




Photométrie

0,5	0,23	50° 5000	1203 500
1,0	0,47	50° 5000	3106 1406
1,5	0,70	50° 5000	1398 647
2,0	0,94	50° 5000	751 364
2,5	1,17	50° 5000	500 233
3,0	1,41	50° 5000	347 162

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 26,4°)



MYRIAD ADJ ROUND WHITE 3000K PHDIM WHITE BEZ

Code article 2056208

Concord

Données générales

Nom du produit	MYRIAD ADJ ROUND WHITE 3000K PHDIM WHITE BEZ
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Office, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Numéro virtuel FI	4278800
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	702
Luminaire efficacy (lm/W)	70
LOR (%)	100
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Chromaticité réglable	N
Beam Angle (°)	24
Distribution type	Symmetric
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	344

Caractéristiques électriques

Consommation électrique totale (W)	10
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	240
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Montage de l'appareillage	Integral
Drive current (mA)	250
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	68500

Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK02
Diffuser material	Glass
Largeur (mm)	76
Nominal Product Height (mm)	115
Max. Lamp Diameter (mm) - D	90
Poids (kg)	0.38
Recessed Depth (mm)	115

MYRIAD ADJ ROUND WHITE 3000K PHDIM WHITE BEZ

Code article 2056208

Concord

Emballage

Product EAN number	5025768562084
Longueur simple de l'emballage (cm)	17.5
Largeur simple de l'emballage (cm)	15.0
Packaging single depth (cm)	17.5
DUN14 (inner)	05025768562084
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5