

Bcon XL 85 3k MB glb blk

Code article 2059491

Concord



Integrated LED spotlight, black RAL 9005, compact and minimalist design, ideal for retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 34° medium beam, optics: Polycarbonate lens, colour temperature: 3000K warm white, total system power: 27W, total fixture output: 2950lm, luminaire efficacy: 109lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 700mA, electronic driver, non-dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit track Adaptor, suitable for Global Trac Pro tracks, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø113x165x205mm, weight: 1.66kg.

Atouts techniques

Photométrie

Données générales

Nom du produit	Bcon XL 85 3k MB glb blk
Technologie	LED
Cap/Base	N/A
General application	Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	2950
Luminaire efficacy (lm/W)	109
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	85
Beam Angle (°)	34
Photobiological Risk Group	RG1

Bcon XL 85 3k MB glb blk

Code article 2059491

Concord

Caractéristiques électriques

Consommation électrique totale (W)	27
Primary Supply/Product voltage - min (V)	230.0
Primary Supply/Product voltage - max (V)	240.0
Electrical protection	Class II
Dimmable	No
Drive current (mA)	700
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz

Durée de vie

Lifespan L70 B50 | 72000

Données physiques

Housing colour	Black
IP rating	IP20
IK rating	IK02
Longueur (mm)	195
Largeur (mm)	200
Nominal Product Height (mm)	250

Emballage

Product EAN number	5025768594917
Longueur simple de l'emballage (cm)	25.0
Largeur simple de l'emballage (cm)	19.5
Packaging single depth (cm)	20.5
DUN14 (inner)	5025768594917
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	19.5
Packaging outer depth (cm)	20.5