


BEACON 93CRI 4K MEDIUM BEAM L3+DALI BLACK

Code article 2059644

Concord



Integrated LED spotlight, black RAL 9005, compact and minimalist design, ideal for retail, display, museum and gallery applications, die-cast aluminium body, passive cooling heatsink, beam angle: 38° medium beam, optics: Aluminium reflector, colour temperature: 4000K neutral white, total system power: 21W, total fixture output: 1885lm, luminaire efficacy: 90lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, DALI dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit DALI track adaptor, suitable for Concord Lytespan 3+DALI track, ingress protection rating: IP20. **IMPORTANT NOTE:** This fixture can only be used on the Lytespan DALI or Lytebeam DALI tracks !

Atouts techniques


Dimensions (mm)



Photométrie

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.35	Ø171	16489
		Ø270	7029
1.0	0.69	Ø342	4117
		Ø420	1752
1.5	1.04	Ø420	1830
		Ø510	779
2.0	1.39	Ø510	1029
		Ø600	685
2.5	1.73	Ø600	889
		Ø700	520
3.0	2.08	Ø700	487
		Ø800	396

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 38.2°)



BEACON 93CRI 4K MEDIUM BEAM L3+DALI BLACK

Code article 2059644

Concord

Données générales

Nom du produit	BEACON 93CRI 4K MEDIUM BEAM L3+DALI BLACK
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	1885
Luminaire efficacy (lm/W)	90
LOR (%)	100
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	93
Colour Consistency (SDCM)	3
Chromaticité réglable	N
Beam Angle (°)	38
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	21
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class II
Type d'appareillage	Electronic ballast
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Drive current (mA)	500
Courant d'appel (A)	5
Inrush Duration (µs)	50
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	52
Max. products per 16A C Breaker	85

Durée de vie

Lifespan L70 B50	72000
Lifespan L70 B10	72000
Lifespan L80 B50	72000
Lifespan L80 B20	72000
Lifespan L80 B10	72000
Lifespan L90 B50	43000
Lifespan L90 B20	36000
Lifespan L90 B10	33000

BEACON 93CRI 4K MEDIUM BEAM L3+DALI BLACK

Code article 2059644

Concord

Données physiques

Housing colour	Black
IP rating	IP20
IK rating	IK02
Largeur (mm)	130
Nominal Product Height (mm)	190
Nominal Product Diameter (mm)	80
Poids (kg)	0.7

Emballage

Product EAN number	5025768596447
Longueur simple de l'emballage (cm)	16.0
Largeur simple de l'emballage (cm)	17.6
Packaging single depth (cm)	18.2
DUN14 (inner)	05025768596447
Units per outer package	1
Packaging outer length / height (cm)	16.0
Packaging outer width (cm)	17.6
Packaging outer depth (cm)	18.2

Sécurité

Glow Wire Test (°C)	650
---------------------	-----