

BEACON 85CRI 3K MEDIUM BEAM L3 TRAILING EDGE WHITE

Code article 2059667

Concord



Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 38° medium beam, optics: Aluminium reflector, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 2269lm, luminaire efficacy: 108lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, trailing edge dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x190mm, weight: 0.96kg.

Atouts techniques


Dimensions (mm)



Photométrie

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.35	Ø17	Ø19	1874 800
1.0	0.69	Ø34	Ø38	474 200
1.5	1.04	Ø51	Ø57	210 90
2.0	1.39	Ø68	Ø75	158 64
2.5	1.73	Ø85	Ø94	126 51
3.0	2.08	Ø102	Ø113	103 42

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 38.2°)



BEACON 85CRI 3K MEDIUM BEAM L3 TRAILING EDGE WHITE

Code article 2059667

Concord

Données générales

Nom du produit	BEACON 85CRI 3K MEDIUM BEAM L3 TRAILING EDGE WHITE
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Numéro virtuel FI	4280817
Numéro virtuel SE	7401244
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	2269
Luminaire efficacy (lm/W)	108
LOR (%)	100
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	85
Colour Consistency (SDCM)	3
Chromaticité réglable	N
Beam Angle (°)	38
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	21
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
Electrical protection	Class II
Type d'appareillage	Electronic ballast
Dimmable	Yes
Dimming method	Mains: trailing edge only
Minimum dimming level (%)	3
Drive current (mA)	500
Courant d'appel (A)	45
Inrush Duration (µs)	20
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	48
Max. products per 16A C Breaker	80

Durée de vie

Lifespan L70 B50	72000
Lifespan L70 B10	72000
Lifespan L80 B50	72000
Lifespan L80 B20	72000
Lifespan L80 B10	72000
Lifespan L90 B50	43000
Lifespan L90 B20	36000
Lifespan L90 B10	33000

BEACON 85CRI 3K MEDIUM BEAM L3 TRAILING EDGE WHITE

Code article 2059667

Concord

Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK02
Longueur (mm)	70
Largeur (mm)	130
Nominal Product Height (mm)	169
Poids (kg)	1.543

Emballage

Product EAN number	5025768596676
Longueur simple de l'emballage (cm)	6.299
Largeur simple de l'emballage (cm)	6.929
Packaging single depth (cm)	7.165
DUN14 (inner)	05025768596676
Units per outer package	1
Packaging outer length / height (cm)	6.299
Packaging outer width (cm)	6.929
Packaging outer depth (cm)	7.165

Sécurité

Glow Wire Test (°C)	650
---------------------	-----