


Solstice 100 1525lm 930 SSA01D

Code article 2060854


Concord



The Solstice 100 1525lm 930 SSA01D is a high efficient SYLSMART Connected enabled downlight luminaire, Colour rendering index Ra>90, Colour temperature: 3000K Warm White, Class II, Protection rating IP44/IP20, Cut out dimensions: 100mm

Atouts techniques


Dimensions (mm)



Photométrie

0.5	0.57	50°	50°	5487	2103
1.0	1.15	50°	50°	1934	852
1.5	1.72	50°	50°	722	228
2.0	2.29	50°	50°	406	103
2.5	2.86	50°	50°	280	68
3.0	3.44	50°	50°	180	39

Distance [m] Cone diameter [m]
— C0 - C180 (Half beam angle: 58.6°)



Solstice 100 1525lm 930 SSA01D

Code article 2060854

Concord

Données générales

Nom du produit	Solstice 100 1525lm 930 SSA01D
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Hospitality, Retail
Operating temperature range (°C)	5°C...+35°C
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Numéro virtuel FI	4170475
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	1525
Luminaire efficacy (lm/W)	113
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	60
Distribution type	Symmetric
Glare control	< 20
Photobiological Risk Group	RG0

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	13.5
Actuel (A)	1
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	0.1
Electrical protection	Class II
Control gear required	Yes
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Connected (SSA)
Drive current (mA)	350
Courant d'appel (A)	20
Inrush Duration (µs)	25
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	82
Max. products per 10A B Breaker	82
Max. products per 16A B Breaker	130
Connectable conductor cross section - Min (mm²)	0.5
Connectable conductor cross section - Max (mm²)	1.5

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L90 B50	56000

Solstice 100 1525lm 930 SSA01D

Code article 2060854

Concord

Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP44/20
IK rating	IK03
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Finition réflecteur	High-gloss
Nominal Product Height (mm)	92
Nominal Product Diameter (mm)	112
Built-in diameter (mm)	100
Poids (kg)	0.43

Emballage

Product EAN number	5025768608546
Longueur simple de l'emballage (cm)	13.5
Largeur simple de l'emballage (cm)	13.5
Packaging single depth (cm)	16.5
DUN14 (inner)	05025768608546
Units per outer package	1
Packaging outer length / height (cm)	13.5
Packaging outer width (cm)	13.5
Packaging outer depth (cm)	16.5

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	5-35