


# CONTINUUM PLUS TR 1.2 940 CO UGR D DALI EM W

Code article 2064514

Concord



CONTINUUM PLUS TR 1.2 940 CO UGR D DALI EM W is a linear luminaire with trim body for plasterboard ceilings, suitable for recessed installation either horizontally or vertically, recessed mounting accessory, direct light distribution, compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, white (RAL9016) finishing, extruded aluminium body, 1205x80x85mm dimensions, prismatic diffuser combined with lenses, 4000K (neutral white) colour temperature, total system power: 24W, total fixture output: 3150lm, luminaire efficacy: 131lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, DALI dimmable, 3-hours LiFePO4 integrated DALI Self Test emergency, Class I electrical protection, IP20, IK03, suitable for internal environment only. The product is delivered without diffuser, end cap, suspension or power supply kit, the accessories eg rolled diffuser (2064607) to be ordered separately.

## Atouts techniques

### Dimensions (mm)



### Photométrie

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Illuminance [lx]
0.5	0.71	0.73	2.36'	9790
			2.39'	2660
			2.41'	2580
1.0	1.42	1.46	4.63'	2447
			4.67'	872
			4.71'	820
1.5	2.12	2.19	6.94'	1088
			6.99'	298
			7.03'	286
2.0	2.83	2.92	9.27'	612
			9.31'	168
			9.35'	162
2.5	3.54	3.65	11.60'	362
			11.64'	107
			11.68'	104
3.0	4.25	4.38	13.93'	272
			13.97'	78
			14.01'	72



# CONTINUUM PLUS TR 1.2 940 CO UGR D DALI EM W

Code article 2064514

Concord

## Données générales

Nom du produit	CONTINUUM PLUS TR 1.2 940 CO UGR D DALI EM W
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ceiling recessed mounting
Built in presence detector	NONE
Fixture rating	Enclosed
General application	Office, Education, Retail
Operating temperature range (°C)	1°C...+25°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	3150
Luminaire efficacy (lm/W)	131
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	270

## Caractéristiques électriques

Emergency mode	Maintained
Emergency type	
Emergency duration (h)	3
Consommation électrique totale (W)	24
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Minimum dimming level (%)	1
Drive current (mA)	500
Courant d'appel (A)	13.6
Inrush Duration (µs)	304
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	30
Max. products per 13A C Breaker	38
Max. products per 16A C Breaker	46
Max. products per 20A C Breaker	58
Max. products per 10A B Breaker	18
Max. products per 13A B Breaker	23
Max. products per 16A B Breaker	28
Max. products per 20A B Breaker	35
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.75
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

# CONTINUUM PLUS TR 1.2 940 CO UGR D DALI EM W

Code article 2064514

Concord

## Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	89000

## Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Finition réflecteur	Not Applicable
Longueur (mm)	1205
Largeur (mm)	80
Nominal Product Height (mm)	85
Poids (kg)	3.6

## Emballage

Product EAN number	5025768645145
Longueur simple de l'emballage (cm)	131.0
Largeur simple de l'emballage (cm)	11.7
Packaging single depth (cm)	14.7
DUN14 (inner)	05025768645145
Units per outer package	1
Packaging outer length / height (cm)	131.0
Packaging outer width (cm)	11.7
Packaging outer depth (cm)	14.7

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	1-25