

CONTINUUM PLUS 2.7 940 ST OPAL D DALI W

Code article 2064770

Concord



CONTINUUM PLUS 2.7 940 ST OPAL D DALI W is a linear luminaire for surface, ceiling recessed or suspended mounting, with 3 meter pre-wiring and complete with end caps and suspension cables, direct light distribution, compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, white (RAL9016) finishing, extruded aluminium body, 2709x56x85mm dimensions, opal diffuser, 4000K (neutral white) colour temperature, total system power: 47.5W, total fixture output: 6550lm, luminaire efficacy: 138lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 1125mA, electronic driver, DALI dimmable, Class I electrical protection, IP20, IK03, suitable for internal environment only.

Atouts techniques


Dimensions (mm)



Photométrie

| Distance [m] | Cone diameter [m] | Beam angle [°] | Beam angle [°] | Beam angle [°] | Illuminance [lx] |
|--------------|-------------------|----------------|----------------|----------------|-----------------------|
| 0.5 | 1.23 1.31 | 50° | 50° | 50° | 10011 1289 1152 |
| 1.0 | 2.45 2.62 | 50° | 50° | 50° | 2503 317 281 |
| 1.5 | 3.68 3.92 | 50° | 50° | 50° | 1112 141 125 |
| 2.0 | 4.90 5.23 | 50° | 50° | 50° | 655 84 72 |
| 2.5 | 6.13 6.54 | 50° | 50° | 50° | 450 57 48 |
| 3.0 | 7.36 7.85 | 50° | 50° | 50° | 270 34 21 |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 105.2°)
 — C90 - C270 (Half beam angle: 101.6°)



CONTINUUM PLUS 2.7 940 ST OPAL D DALI W

Code article 2064770

Concord

Données générales

| | |
|----------------------------------|--|
| Nom du produit | CONTINUUM PLUS 2.7 940 ST OPAL D DALI W |
| Technologie | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Montage | Suspended, Ceiling surface mounting, Ceiling recessed mounting |
| Built in presence detector | NONE |
| Fixture rating | Enclosed |
| General application | Office, Education, Retail |
| Operating temperature range (°C) | 1°C...+25°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002892 |
| Warranty | 5 ans |

Données optiques

| | |
|---------------------------------|---------------|
| Fixture luminous flux (lm) | 6550 |
| Luminaire efficacy (lm/W) | 138 |
| Température de couleur (K) | 4000 |
| Couleur de lumière | Neutral White |
| IRC (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Distribution type | Symmetric |
| Glare control | < 25 |
| Photobiological Risk Group | RG1 |

Caractéristiques électriques

| | |
|--|---------------------------------|
| Emergency type | |
| Consommation électrique totale (W) | 47.5 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.98 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 10 |
| Electrical protection | Class I |
| Control gear required | No |
| Type d'appareillage | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI-2 |
| Minimum dimming level (%) | 1 |
| Drive current (mA) | 1125 |
| Courant d'appel (A) | 35 |
| Inrush Duration (µs) | 170 |
| Energy Efficiency Class (A->G) of contained light source | B, C (more than 1 Light Source) |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Ultra low (5% or less) |
| Max. products per 10A C Breaker | 30 |
| Max. products per 13A C Breaker | 38 |
| Max. products per 16A C Breaker | 46 |
| Max. products per 20A C Breaker | 58 |
| Max. products per 10A B Breaker | 18 |
| Max. products per 13A B Breaker | 23 |
| Max. products per 16A B Breaker | 28 |
| Max. products per 20A B Breaker | 35 |
| Connectable conductor cross section - Min (mm ²) | 0.75 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

CONTINUUM PLUS 2.7 940 ST OPAL D DALI W

Code article 2064770

Concord

Durée de vie

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 89000 |

Données physiques

| | |
|-----------------------------|----------------------------------|
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Opal |
| Diffuser material | PC Polycarbonate |
| Finition réflecteur | Not Applicable |
| Longueur (mm) | 2709 |
| Largeur (mm) | 56 |
| Nominal Product Height (mm) | 85 |
| Poids (kg) | 7.2 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5025768647705 |
| Longueur simple de l'emballage (cm) | 281.0 |
| Largeur simple de l'emballage (cm) | 11.7 |
| Packaging single depth (cm) | 14.7 |
| DUN14 (inner) | 05025768647705 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 281.0 |
| Packaging outer width (cm) | 11.7 |
| Packaging outer depth (cm) | 14.7 |

Sécurité

| | |
|--|------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (°C) | 1-25 |