


Colossal 900mm 940 Opal Dir White SSA03

Code article 2071416

Concord



900mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with polycarbonate opal diffuser. Direct light distribution, 9275lm luminous flux, 76.8W system power, 121lm/W luminaire efficacy. Sylsmart Connected enabled. Colour rendering index Ra >90, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40/IP20, IK03. 450mA drive current. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.

Atouts techniques

Dimensions (mm)



Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Illuminance [lx]
0.5	1.42	50°	1.42	1340
1.0	2.84	50°	2.84	335
1.5	4.25	50°	4.25	149
2.0	5.67	50°	5.67	84
2.5	7.09	50°	7.09	53
3.0	8.51	50°	8.51	36

Distance [m] Cone diameter [m]
Beam angle: 50° (Half beam angle: 25°)



Colossal 900mm 940 Opal Dir White SSA03

Code article 2071416

Concord

Données générales

Nom du produit	Colossal 900mm 940 Opal Dir White SSA03
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ceiling surface mounting
Built in presence detector	PIR
General application	Hospitality, Office
Operating temperature range (°C)	5°C...+25°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	9275
Luminaire efficacy (lm/W)	121
Température de couleur (K)	4000
Colour Code	940
Couleur de lumière	Neutral White
IRC (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	76.8
Actuel (A)	450
Primary Supply/Product voltage - min (V)	198.0
Primary Supply/Product voltage - max (V)	264.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Connected (SSA)
Drive current (mA)	450
Courant d'appel (A)	27
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	15
Max. products per 16A C Breaker	24
Max. products per 20A C Breaker	37
Max. products per 10A B Breaker	25
Max. products per 16A B Breaker	40
Max. products per 20A B Breaker	62
Connectable conductor cross section - Min (mm²)	1.5
Connectable conductor cross section - Max (mm²)	2.5

Durée de vie

Lifespan L70 B50	170000
Lifespan L80 B20	145000
Lifespan L90 B10	66000

Colossal 900mm 940 Opal Dir White SSA03

Code article 2071416

Concord

Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	93
Nominal Product Diameter (mm)	888
Poids (kg)	16.7

Emballage

Product EAN number	5025768714162
Longueur simple de l'emballage (cm)	14.0
Largeur simple de l'emballage (cm)	96.0
Packaging single depth (cm)	96.0
DUN14 (inner)	05025768714162
Units per outer package	1
Packaging outer length / height (cm)	14.0
Packaging outer width (cm)	96.0
Packaging outer depth (cm)	96.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	5-25