


# Beacon XL Muse 3000K DALI L3 ST Adaptor White

Code article 2692777


Concord



Integrated LED spotlight, white, unique soft-touch ring, adjustable beam angle from a 10 spot to a 70 flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 10 spot to 70 flood, optics: aspheric glass lens, colour temperature: 3000K warm white, total system power: 41W, total fixture output: 2544lm, luminaire efficacy: 62lm/W, LOR: 100%, super high colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1050mA, electronic driver, DALI dimmable, power factor: 0.95, Stucchi DALI Adaptor. Compatible with OneTrack (for detailed information please check the compatibility list).

## Atouts techniques


### Dimensions (mm)



### Photométrie

Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.00	4912
1.0	0.00	1228
1.5	0.00	545
2.0	0.00	307
2.5	0.00	195
3.0	0.00	128

Distance [m] Cone diameter [m] Illuminance [lx]  
 — C0 - C180 (Half beam angle: 0.0°)



# Beacon XL Muse 3000K DALI L3 ST Adaptor White

Code article 2692777

Concord

## Données générales

Nom du produit	Beacon XL Muse 3000K DALI L3 ST Adaptor White
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Track mounting
Built in presence detector	NONE
Environment	Internal
General application	Museums & Galleries, Retail
Operating temperature range (°C)	25°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	2544
Luminaire efficacy (lm/W)	62
LOR (%)	100
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	97
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	SDCM3
Chromaticité réglable	N
Distribution type	Symmetric
Photobiological Risk Group	RG0

## Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	41
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	1
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	1050
Courant d'appel (A)	30
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	12
Max. products per 16A C Breaker	32
Max. products per 20A C Breaker	38
Max. products per 10A B Breaker	12
Max. products per 16A B Breaker	20

## Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK02
Diffuser finish	Bezel (or Ring)
Diffuser material	Glass
Finition réflecteur	Not Applicable
Largeur (mm)	165
Nominal Product Height (mm)	200
Nominal Product Diameter (mm)	114
Poids (kg)	1.7

# Beacon XL Muse 3000K DALI L3 ST Adaptor White

Code article 2692777

**Concord**

## Emballage

Product EAN number	5025768927777
Longueur simple de l'emballage (cm)	25.0
Largeur simple de l'emballage (cm)	19.5
Packaging single depth (cm)	20.0
DUN14 (inner)	05025768927777
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	19.5
Packaging outer depth (cm)	20.0

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	25-25
Utilisation pour applications sèches uniquement	Yes