

Syl-Lighter LED II 220 RO 21W NW

Code article 3031817

SYLVANIA

Données générales

Nom du produit	Syl-Lighter LED II 220 RO 21W NW
Technologie	LED
Housing	Aluminium
Montage	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
Operating temperature range (°C)	-10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Numéro virtuel SE	7467167
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	1989
Luminaire efficacy (lm/W)	95
LOR (%)	100
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Chromaticité réglable	N
Beam Angle (°)	74
Distribution type	Symmetric
Glare control	< 24
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	21
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	600
Courant d'appel (A)	6.44
Inrush Duration (µs)	830
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	20
Max. products per 13A C Breaker	26
Max. products per 16A C Breaker	32
Max. products per 20A C Breaker	40
Durée de vie	
Lifespan L70 B50	100000
Lifespan L80 B20	74000
Lifespan L90 B10	34000

Syl-Lighter LED II 220 RO 21W NW

Code article 3031817

SYLVANIA

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Finition réflecteur	High-gloss
Nominal Product Height (mm)	60
Nominal Product Diameter (mm)	220
Poids (kg)	0.72
Recessed Depth (mm)	150

Emballage

Product EAN number	8711971318170
Longueur simple de l'emballage (cm)	25.0
Largeur simple de l'emballage (cm)	25.0
Packaging single depth (cm)	7.5
DUN14 (inner)	18711971318177
Units per outer package	12
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	52.0
Packaging outer depth (cm)	26.0

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-10-25