



# Insaver HO Topper LED II 225 RO 25W NW

Code article 3033949

**SYLVANIA**

## Données générales

Nom du produit	Insaver HO Topper LED II 225 RO 25W NW
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ceiling recessed mounting
Environment	Interior
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Numéro virtuel SE	7465634
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	2400
Luminaire efficacy (lm/W)	104
LOR (%)	100
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Chromaticité réglable	N
Beam Angle (°)	74
Distribution type	Symmetric
Glare control	< 24
Photobiological Risk Group	RG0

## Caractéristiques électriques

Consommation électrique totale (W)	25
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	630
Courant d'appel (A)	6.44
Inrush Duration (µs)	830
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	12
Max. products per 13A C Breaker	16
Max. products per 16A C Breaker	20
Max. products per 20A C Breaker	25

## Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	74000
Lifespan L90 B10	34000

# Insaver HO Topper LED II 225 RO 25W NW

Code article 3033949

**SYLVANIA**

## Données physiques

Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Finition réflecteur	High-gloss
Nominal Product Height (mm)	65
Nominal Product Diameter (mm)	240
Poids (kg)	0.845
Recessed Depth (mm)	150

## Emballage

Product EAN number	8711971339496
Longueur simple de l'emballage (cm)	27.2
Largeur simple de l'emballage (cm)	27.3
Packaging single depth (cm)	8.0
DUN14 (inner)	18711971339493
Units per outer package	12
Packaging outer length / height (cm)	56.6
Packaging outer width (cm)	56.7
Packaging outer depth (cm)	28.0

## Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-10-25