

OT H-Trk Ready Joiner 940 DALI Blk H32C1405/b6-o-2

Code article 9200425

Concord

Données générales

Nom du produit	OT H-Trk Ready Joiner 940 DALI Blk H32C1405/b6-o-2
Technologie	LED
Cap/Base	N/A
Montage	Suspended
Built in presence detector	NONE
Operating temperature range (°C)	1°C...+25°C
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	2600
Luminaire efficacy (lm/W)	75
LOR (%)	100
Colour Code	940
Couleur de lumière	Neutral White
IRC (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	112
Distribution type	Diffuse
Photobiological Risk Group	RG0

Caractéristiques électriques

Emergency type	
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Courant d'appel (A)	10
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	F
Max. products per 10A C Breaker	31
Max. products per 16A C Breaker	51
Max. products per 16A B Breaker	30
Connectable conductor cross section - Min (mm²)	7.5
Connectable conductor cross section - Max (mm²)	7.5

Données physiques

Housing colour	Black
IP rating	IP20
IK rating	IK02
Longueur (mm)	1405
Largeur (mm)	31.4
Nominal Product Height (mm)	83
Poids (kg)	4.0

OT H-Trk Ready Joiner 940 DALI Blk H32C1405/b6-o-2

Code article 9200425

Concord

Emballage

Description de l'emballage	Carton
Product EAN number	4012289004255
Longueur simple de l'emballage (cm)	10.0
Largeur simple de l'emballage (cm)	10.0
Packaging single depth (cm)	150.0
Units per outer package	1
Packaging outer length / height (cm)	10.0
Packaging outer width (cm)	10.0
Packaging outer depth (cm)	150.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	1-25