

SYISMART SALVADOR 2016 SSC

Code article V960012

SYLVANIA



The Salvador Series 2000 DALI controller seamlessly integrates up to 16 wired DALI drivers into the SylSmart Standalone system. When integrated, DALI luminaires appear as luminaires in the SylSmart Standalone network. The SylSmart Salvador 2016 supports industry standards such as DALI D4i, DALI DT6, and DALI DT8.

Atouts techniques

Photométrie

Données générales

Nom du produit	SYISMART SALVADOR 2016 SSC
Technologie	Electronic Device
Type of accessory	Control
Virtual assistant compatibility	N/A
ETIM Class	EC000533
Warranty	5 ans

Caractéristiques électriques

Primary Supply/Product voltage - min (V)	100.0
Primary Supply/Product voltage - max (V)	277.0
Dimmable	Yes
Dimming method	DALI-2
Max. drive current (mA)	70
Drive current - Range (mA)	/ 70mA
Courant d'appel (A)	20
Nominal Frequency (Hz)	50/60Hz

Données physiques

IP rating	IP20
Longueur (mm)	106
Largeur (mm)	67
Nominal Product Height (mm)	28
Poids (kg)	0.12

Emballage

Longueur simple de l'emballage (cm)	14.0
Largeur simple de l'emballage (cm)	7.0
Packaging single depth (cm)	3.5
Units per outer package	1
Packaging outer length / height (cm)	14.0
Packaging outer width (cm)	7.0
Packaging outer depth (cm)	3.5