


| Distance [m] | Cone diameter [m] | Beam angle [°] | Beam diameter [m] | Beam diameter [in] | Illuminance [lx] |
|--------------|-------------------|----------------|-------------------|--------------------|------------------|
| 0.5          | 0.79<br>0.76      | 50°<br>48°     | 158.2"<br>152.4"  | 170<br>177         | 7021             |
| 1.0          | 1.57<br>1.53      | 50°<br>48°     | 316.4"<br>304.8"  | 340<br>354         | 1770             |
| 1.5          | 2.36<br>2.29      | 50°<br>48°     | 474.6"<br>457.2"  | 510<br>494         | 787              |
| 2.0          | 3.15<br>3.06      | 50°<br>48°     | 632.8"<br>610.2"  | 680<br>656         | 443              |
| 2.5          | 3.93<br>3.82      | 50°<br>48°     | 796.0"<br>768.5"  | 860<br>825         | 354              |
| 3.0          | 4.72<br>4.59      | 50°<br>48°     | 959.2"<br>918.7"  | 1040<br>994        | 293              |
|              |                   | 50°<br>48°     | 38.2"<br>37.4"    | 48<br>46           | 191              |
|              |                   | 50°<br>48°     | 38.2"<br>37.4"    | 48<br>46           | 191              |



\_\_\_\_\_

\_\_\_\_\_