

SylWork Inspection Mini

Artikelnummer 0090202

SYLVANIA

YourHome™



SylWork offers a range of high-performance LED work lights, available in both mains-powered and battery-operated models. Designed for ultimate flexibility, SylWork provides reliable, temporary lighting for a variety of DIY projects, including home decorating, household repairs, cleaning, tidying, and general maintenance tasks. The SylWork Inspection Mini is a portable, battery-operated inspection light, perfect for worksite tasks, camping, and outdoor activities. Its compact design makes it easy to carry, while the built-in hook allows for convenient hands-free use. The light is easily rechargeable with the included USB cable and features three-step dimming along with a flashing mode for emergency situations. Lightweight yet durable, it provides a practical lighting solution for various needs and comes with a three-year warranty. Ideal for both professional and home use.

Technische gegevens

Fotometrie

Algemene gegevens

Productnaam	SylWork Inspection Mini
Technologie	LED
Lampvoet	N/A
Behuizing	ABS Kunststof
Montage	Overige
Geïntegreerde aanwezigheidssensor	NONE
Algemene toepassing	Residentieel & Consument
Omgevingstemperatuur (°C)	-10°C...+40°C
Virtual assistant compatibility	N/A
ETIM klasse	EC000347
Garantie	3 jaar

Optische gegevens

Lumenstroom armatuur (lm)	480
Kleurtemperatuur (K)	6500
Lichtkleur	Koelwit
CRI (Ra)	80
Initiële kleurvariatie (SDCM)	SDCM6
Bundel breedte (°)	120
Type licht distributie	Geen
Fotobiologische risicogroep	RG1

Elektrische gegevens

Nood type	
Totaal energieverbruik (W)	7.5
Elektrische beschermingsklasse	Klasse III
Type ballast	Niet nodig
Dimbaar	Nee
Dimtechnologie	N/A
Energie-efficiëntieklasse (A->G) van de lichtbron in dit product	F
Nominale frequentie (Hz)	DC

Gegevens levensduur

Gemiddelde nominale levensduur - L70 B50	25000
--	-------

Fysieke gegevens

Kleur behuizing	Zwart
IP waarde	IP54
IK waarde	IK06
Afwerking diffusor	Prismatisch, Transparant
Materiaal diffusor	PC Polycarbonaat
Afwerking reflector	Not Applicable
Lengte (mm)	337.5
Breedte (mm)	30
Hoogte (mm)	30
Gewicht (kg)	0.192

Verpakkingen

EAN code	5410288902029
Enkele lengte verpakking (cm)	34.5
Enkele breedte verpakking (cm)	4.0
Hoogte eenheidsverpakking (cm)	3.5
DUN14 (inner)	15410288902026
Eenheden per omdoos	40
Lengte omdoos (cm)	39.0
Breedte omdoos (cm)	19.5
Diepte omdoos (cm)	38.5

Veiligheidsgegevens

Gloeidraad test (°)	650
Optimale bedrijfsomstandigheden (°C)	-10-40