

TOLEDO MICROLYNX FROSTED 470LM 840

Item No: 0026809

SYLVANIA



ToLEDo Microlynx LED is the perfect replacement for GX53 CFL lampCompact design 15,000 hours rated life Higher lumen output Good colour rendering - CRI80 Non-dimmable 3 years warrantyPerfect for kitchen cabinets, showcases, display units and wardrobes

Technical Assets

Photometrics

General data

Nome do produto	TOLEDO MICROLYNX FROSTED 470LM 840
Tecnologia	LED
Watt (Rated) (W)	5
Casquilho	GX53
Luminária	Open
Aplicação geral	Hotelaria, Residencial & Consumer
Performance ambient temperature Tq (°C)	25
ETIM	EC001959
E-number FI	4740839
Garantia	3 years

Optical data

Useful luminous flux (Φuse)	470
Luminous flux (Rated) (lm)	470
Temperatura de cor (K)	4000
Cor da luz	Cool White
CRI	80
Lumen maintenance at end of nominal life (%)	70

TOLEDO MICROLYNX FROSTED 470LM 840

Item No: 0026809

SYLVANIA

Electrical data

Power consumption (W)	5
Potência	5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Fator de potência	0.5
No. Of switching cycles before premature failures	>50000
Corrente de arranque (A)	2
Frequência nominal (Hz)	50/60Hz
Máx. dispositivos por disjuntor C de 10A	208
Máx. produtos por disjuntor C de 16A	334
Max. products per 20A C Breaker	418

Lifetime data

Vida média (horas)	15000
Average life (Rated) (h)	15000

Physical data

Comprimento nominal do produto (mm)	74.3
Nominal Product Diameter (mm)	25
Peso (kg)	0.048

Packaging

Código EAN	5410288268095
Comprimento / altura da embalagem individual (cm)	7.6
Largura da embalagem individual (cm)	2.7
Profundidade da embalagem individual (cm)	7.6
DUN14 (inner)	15410288268092
Units per inner package	6
DUN14 (outer)	25410288268099
Unidades por embalagem exterior	6
Comprimento / altura da embalagem exterior (cm)	16.0
Largura da embalagem exterior (cm)	9.0
Profundidade da embalagem exterior (cm)	8.4

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures