

ToLED_o SUPERIA T5 AC 5FT 4000LM 840

Item No: 0028040

SYLVANIA



50,000 hours average rated lifetime (L70 F50) Last 2.5 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp
High switching cycles - 200,000X High lumen efficacy - 154lm/W
Omni-directional light distribution and wide beam angle
Minimum and maximum operating temperature: -20°C to 50°C
Glass construction and polycarbonate end-caps
Only suitable for direct mains (AC 220-240V) operation
Ideal for factories, parking lots, supermarkets, department stores, schools and offices
Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

Technical Assets

Photometrics

General data

Nome do produto	ToLED _o SUPERIA T5 AC 5FT 4000LM 840
Tecnologia	LED
Watt (Rated) (W)	26
Casquilho	G5
Aplicação geral	Escritórios, Hotelaria, Logistics & Industry, Retalho, Residential & Consumer, Museums & Galleries, Educação
ETIM	EC001959
E-number FI	4740765
Garantia	5 anos

Optical data

Luminous flux (Rated) (lm)	4000
Temperatura de cor (K)	4000
Cor da luz	Cool White
CRI	80
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	26
Potência	26
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<2
Fator de potência	0.9
No. Of switching cycles before premature failures	>200000
Regulável	No

Lifetime data

Vida média (horas)	50000
Average life (Rated) (h)	50000

Physical data

Peso (kg)	0.174
-----------	-------

ToLEDo SUPERIA T5 AC 5FT 4000LM 840

Item No: 0028040



Packaging

Código EAN	5410288280400
Comprimento / altura da embalagem individual (cm)	146.2
Largura da embalagem individual (cm)	1.8
Profundidade da embalagem individual (cm)	1.8
DUN14 (inner)	15410288280407
Unidades por embalagem exterior	10
Comprimento / altura da embalagem exterior (cm)	152.5
Largura da embalagem exterior (cm)	15.6
Profundidade da embalagem exterior (cm)	8.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture