

RefLED Sup RT ES50 V2 360 DIM 865 36d SL

Item No: 0028552

SYLVANIA




- Premium performance professional LED GU10 range with the same look and feel of traditional halogen GU10 lamp
- Recreates backlight effect similar to halogen dichroic lamps
- Full glass design - means no colours clashing between lamp and fixture
- Very long lifetime of up to 25,000 hours
- COOLFIT functionality – ensures overheat and over temperature protection
- High switching cycles: >100,000
- High colour rendering: CRI80
- Dimmable on approved dimmers.
- Warranty: 5 Years

Technical Assets

Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.35 0.36	0.07	0.07	240
		E/C90 18.0°	E/C90 18.0°	1040
		E/C90 20.0°	E/C90 20.0°	1007
1.0	0.71 0.72	0.07	0.07	633
		E/C90 18.0°	E/C90 18.0°	281
		E/C90 20.0°	E/C90 20.0°	259
1.5	1.06 1.08	0.07	0.07	277
		E/C90 18.0°	E/C90 18.0°	116
		E/C90 20.0°	E/C90 20.0°	116
2.0	1.42 1.46	0.07	0.07	156
		E/C90 18.0°	E/C90 18.0°	66
		E/C90 20.0°	E/C90 20.0°	66
2.5	1.77 1.82	0.07	0.07	100
		E/C90 18.0°	E/C90 18.0°	44
		E/C90 20.0°	E/C90 20.0°	41
3.0	2.12 2.18	0.07	0.07	69
		E/C90 18.0°	E/C90 18.0°	31
		E/C90 20.0°	E/C90 20.0°	29

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 40.0°)
 — C90 - C270 (Half beam angle: 39.0°)



RefLED Sup RT ES50 V2 360 DIM 865 36d SL

Item No: 0028552

SYLVANIA

General data

Nome do produto	RefLED Sup RT ES50 V2 360 DIM 865 36d SL
Tecnologia	LED
Watt (Rated) (W)	4.5
Casquilho	GU10
Luminária	Open
Aplicação geral	Educação, Hotelaria, Museums & Galleries, Escritórios, Residential & Consumer, Retalho
Performance ambient temperature Tq (°C)	25
ETIM	EC001959
E-number FI	4740851
Garantia	5 anos

Optical data

Useful luminous flux (Φ_{use})	360
Temperatura de cor (K)	6500
Cor da luz	Daylight
CRI	80
Colour Consistency (SDCM)	6
Variação da cor (SDCM)	SDCM6
Luminous Intensity (cd)	750
Ângulo do feixe (°)	36
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	4.5
Potência	4.5
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<1
Fator de potência	0.7
No. Of switching cycles before premature failures	>100000
Corrente de arranque (A)	0.55
Frequência nominal (Hz)	50Hz
Máx. dispositivos por disjuntor C de 10A	73
Máx. produtos por disjuntor C de 16A	115
Max. products per 20A C Breaker	145

Lifetime data

Vida média (horas)	25000
Average life (Rated) (h)	25000

Physical data

Comprimento nominal do produto (mm)	54
Nominal Product Diameter (mm)	50
Peso (kg)	0.055

RefLED Sup RT ES50 V2 360 DIM 865 36d SL

Item No: 0028552

SYLVANIA

Packaging

Código EAN	5410288285528
Comprimento / altura da embalagem individual (cm)	6.7
Largura da embalagem individual (cm)	5.1
Profundidade da embalagem individual (cm)	5.1
DUN14 (inner)	15410288285525
Units per inner package	6
Packaging inner length / height (cm)	7.5
Packaging inner width (cm)	16.5
Packaging inner depth (cm)	11.0
DUN14 (outer)	25410288285522
Unidades por embalagem exterior	60
Comprimento / altura da embalagem exterior (cm)	17.5
Largura da embalagem exterior (cm)	58.0
Profundidade da embalagem exterior (cm)	17.8

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers