

REFLED SUPERIA RETRO ES50 345LM 827 36° SL

Item No: 0029950

SYLVANIA




- Premium performance professional LED GU10 range with the same look and feel of traditional halogen GU10 lamp
- Recreates backlight effect similar to halogen dichroic lamps
- Full glass design - means no colours clashing between lamp and fixture
- Very long lifetime of up to 25,000 hours
- COOLFIT functionality – ensures overheat and over temperature protection
- High switching cycles: >100,000
- High colour rendering: CRI80
- Non dimmable
- Warranty: 5 Years

Technical Assets

Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.31 0.32	0.31 0.32	2637 1234 1237
1.0	0.63 0.63	0.63 0.63	709 309 309
1.5	0.94 0.95	0.94 0.95	315 137 137
2.0	1.26 1.26	1.26 1.26	177 77 77
2.5	1.57 1.56	1.57 1.56	113 68 68
3.0	1.88 1.88	1.88 1.88	79 54 54

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 26.9°)
 — C90 - C270 (Half beam angle: 34.9°)



REFLED SUPERIA RETRO ES50 345LM 827 36° SL

Item No: 0029950

SYLVANIA

General data

Nome do produto	REFLED SUPERIA RETRO ES50 345LM 827 36° SL
Tecnologia	LED
Watt (Rated) (W)	4
Casquilho	GU10
Luminária	Open
Aplicação geral	Educação, Hotelaria, Museums & Galleries, Escritórios, Residential & Consumer, Retalho
Performance ambient temperature Tq (°C)	25
ETIM	EC001959
E-number FI	4740684
Garantia	5 anos

Optical data

Useful luminous flux (Φ_{use})	345
Temperatura de cor (K)	2700
Cor da luz	Homelight
CRI	80
Varição da cor (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	700
Ângulo do feixe (°)	36
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	4
Potência	4
Equivalent watt (W)	50
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<1
Fator de potência	0.55
No. Of switching cycles before premature failures	>100000
Regulável	No
Corrente de arranque (A)	3.4
Frequência nominal (Hz)	50/60Hz
Máx. dispositivos por disjuntor C de 10A	13
Máx. produtos por disjuntor C de 16A	21
Max. products per 20A C Breaker	26

Lifetime data

Vida média (horas)	25000
Average life (Rated) (h)	25000

Physical data

Comprimento nominal do produto (mm)	54
Nominal Product Diameter (mm)	50
Peso (kg)	0.048

REFLED SUPERIA RETRO ES50 345LM 827 36° SL

Item No: 0029950

SYLVANIA

Packaging

Código EAN	5410288299501
Comprimento / altura da embalagem individual (cm)	5.1
Largura da embalagem individual (cm)	5.1
Profundidade da embalagem individual (cm)	6.7
DUN14 (inner)	15410288299508
Units per inner package	6
Packaging inner length / height (cm)	11.0
Packaging inner width (cm)	16.4
Packaging inner depth (cm)	8.1
DUN14 (outer)	25410288299505
Unidades por embalagem exterior	60
Comprimento / altura da embalagem exterior (cm)	58.6
Largura da embalagem exterior (cm)	18.6
Profundidade da embalagem exterior (cm)	18.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	None