

Resisto 1200 IP66 1700-2900lm 865

Item No: 0010446

SYLVANIA


PROTM



Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform light appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time, IP66, IK08, Class I, SDCM<3, 6500K, CRI>80, non-dimmable, 1700 / 2100 / 2500 / 2900lm (4 different steps selectable with DIP switches), 10 / 12 / 15 / 17W, 170 / 175 / 167 / 171lm/W depends on setting, 100.000hrs L80B10 lifespan, 1200 x 89 x 88mm (L x W x H) dimensions, 1.35kg weight, operating temperature range from -20 to +40°C. D-mark, ENEC certification.


Technical Assets

Dimensions (mm)



Photometrics

Distance (m)	Cone diameter (m)	Beam angle (°)	Beam diameter (m)	Beam diameter (ft)	Beam diameter (in)	Illuminance (lx)
0.5	1.27	140	1.27	4.17	16.73	2274
1.0	2.54	140	2.54	8.33	33.46	568
1.5	3.81	140	3.81	12.50	50.19	233
2.0	5.08	140	5.08	16.67	66.92	142
2.5	6.35	140	6.35	20.83	83.65	91
3.0	7.62	140	7.62	25.00	100.38	60
3.5	8.89	140	8.89	29.17	117.11	44
4.0	10.16	140	10.16	33.33	133.84	33
4.5	11.43	140	11.43	37.50	150.57	25
5.0	12.70	140	12.70	41.67	167.30	19
5.5	13.97	140	13.97	45.83	184.03	14
6.0	15.24	140	15.24	50.00	200.76	11
6.5	16.51	140	16.51	54.17	217.49	9
7.0	17.78	140	17.78	58.33	234.22	8
7.5	19.05	140	19.05	62.50	250.95	7
8.0	20.32	140	20.32	66.67	267.68	6
8.5	21.59	140	21.59	70.83	284.41	5
9.0	22.86	140	22.86	75.00	301.14	4
9.5	24.13	140	24.13	79.17	317.87	3
10.0	25.40	140	25.40	83.33	334.60	2



Resisto 1200 IP66 1700-2900lm 865

Item No: 0010446

SYLVANIA

General data

Product name	Resisto 1200 IP66 1700-2900lm 865
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
E-number FI	4357214
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2900
Luminaire efficacy (lm/W)	175
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	110
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Emergency type	
Total power consumption (W)	17
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	9
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Inrush Current (A)	8.6
Inrush Duration (µs)	278
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	54
Max. products per 13A C Breaker	71
Max. products per 16A C Breaker	87
Max. products per 20A C Breaker	109
Max. products per 10A B Breaker	33
Max. products per 13A B Breaker	42
Max. products per 16A B Breaker	52
Max. products per 20A B Breaker	65
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

Resisto 1200 IP66 1700-2900lm 865

Item No: 0010446

SYLVANIA

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L80 B20	100000
Lifespan L80 B10	100000
Lifespan L90 B50	77000

Physical data

Housing colour	RAL 7035 - Light grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1200
Nominal Product Width (mm)	89
Nominal Product Height (mm)	88
Weight (kg)	1.35

Packaging

Product EAN number	5410288104461
Packaging single length / height (cm)	121.0
Packaging single width (cm)	10.3
Packaging single depth (cm)	8.8
DUN14 (inner)	15410288104468
Units per outer package	6
Packaging outer length / height (cm)	122.5
Packaging outer width (cm)	28.0
Packaging outer depth (cm)	22.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40