


Resisto 1500 IP66 4350-7600lm 840 MW ON/OFF

Item No: 0010461

SYLVANIA


PROTM



Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform light appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time, IP66, IK08, Class I, SDCM<3, 4000K, CRI>80, non-dimmable, 4350 / 5200 / 6300 / 7600lm (4 different steps selectable with DIP switches), 24 / 28 / 35 / 42W, 181 / 186 / 180 / 181lm/W depends on setting, 100.000hrs L80B10 lifespan, 1500 x 89 x 88mm (L x W x H) dimensions, 1.76kg weight, operating temperature range from -20 to +40°C. D-mark, ENEC certification. Supplied with integrated Microwave On/Off sensor.


Technical Assets

Dimensions (mm)



Photometrics

Distance (m)	Cone diameter (m)	Beam angle (°)	Beam diameter (m)	Beam diameter (ft)	Beam diameter (in)	Illuminance (lx)
0.5	1.33	120°	1.33	4.36	175	8000
1.0	2.67	120°	2.67	8.75	350	2000
1.5	4.01	120°	4.01	13.12	525	800
2.0	5.34	120°	5.34	17.50	700	400
2.5	6.67	120°	6.67	21.88	875	256
3.0	8.01	120°	8.01	26.25	1050	1600



Resisto 1500 IP66 4350-7600lm 840 MW ON/OFF

Item No: 0010461

SYLVANIA

General data

Product name	Resisto 1500 IP66 4350-7600lm 840 MW ON/OFF
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Built in presence detector	MICROWAVE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
E-number FI	4357229
Warranty	5 years

Optical data

Fixture luminous flux (lm)	7600
Luminaire efficacy (lm/W)	186
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	110
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Emergency type	
Total power consumption (W)	42
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Inrush Current (A)	16.3
Inrush Duration (µs)	234
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	32
Max. products per 13A C Breaker	41
Max. products per 16A C Breaker	51
Max. products per 20A C Breaker	64
Max. products per 10A B Breaker	22
Max. products per 13A B Breaker	28
Max. products per 16A B Breaker	35
Max. products per 20A B Breaker	44
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

Resisto 1500 IP66 4350-7600lm 840 MW ON/OFF

Item No: 0010461



Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L80 B20	100000
Lifespan L80 B10	100000
Lifespan L90 B50	77000

Physical data

Housing colour	RAL 7035 - Light grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	89
Nominal Product Height (mm)	88
Weight (kg)	1.76

Packaging

Product EAN number	5410288104614
Packaging single length / height (cm)	151.0
Packaging single width (cm)	10.3
Packaging single depth (cm)	8.8
DUN14 (inner)	15410288104611
Units per outer package	6
Packaging outer length / height (cm)	152.5
Packaging outer width (cm)	28.0
Packaging outer depth (cm)	22.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40