


Insaver Slim 175 IP54 DALI 1525lm 830

Item No: 0030350

SYLVANIA


PROTM



Insaver Slim is a ceiling recessed LED downlight (IP54 from the front), Die-cast aluminium body, loop in loop out connector for quick installation, Dimmable DALI driver of TRIDONIC (LCA 17W 250–700mA one4all SR PRE 28000670), 13W; 1525lm; 117lm/W; 3000K; UGR <19 with shallow product depth 60mm. Meets TP(a) requirements.

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.55	0.57	5538
1.0	1.16	1.21	1427
1.5	1.75	1.83	646
2.0	2.33	2.44	364
2.5	2.91	3.04	233
3.0	3.48	3.61	162

— C0 - C180 (Half beam angle: 60.4°)



Insaver Slim 175 IP54 DALI 1525lm 830

Item No: 0030350

SYLVANIA

General data

Product name	Insaver Slim 175 IP54 DALI 1525lm 830
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Built in presence detector	NONE
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	40
Virtual assistant compatibility	N/A
ETIM Class	EC001744
E-number FI	4278073
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1525
Luminaire efficacy (lm/W)	117
Correlated colour temperature (k)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	61
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	13
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	9
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2, Switch-dim (mains-rated)
Minimum dimming level (%)	1
Drive current (mA)	390
Inrush Current (A)	18
Inrush Duration (µs)	140
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	36
Max. products per 13A C Breaker	50
Max. products per 16A C Breaker	60
Max. products per 20A C Breaker	76
Max. products per 10A B Breaker	22
Max. products per 13A B Breaker	30
Max. products per 16A B Breaker	36
Max. products per 20A B Breaker	46
Connectable conductor cross section - Min (mm ²)	0.31
Connectable conductor cross section - Max (mm ²)	1.31

Lifetime data

Lifespan L70 B50	90000
Lifespan L80 B20	90000
Lifespan L90 B10	39000

Insaver Slim 175 IP54 DALI 1525lm 830

Item No: 0030350

SYLVANIA

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Reflector finish	Not Applicable
Nominal Product Height (mm)	60
Nominal Product Diameter (mm)	193
Weight (kg)	0.55
Recessed Depth (mm)	150

Packaging

Product EAN number	5410288303505
Packaging single length / height (cm)	20.5
Packaging single width (cm)	20.5
Packaging single depth (cm)	7.3
DUN14 (inner)	15410288303502
Units per outer package	16
Packaging outer length / height (cm)	42.5
Packaging outer width (cm)	42.5
Packaging outer depth (cm)	31.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-10-40