


OPTICLIP R 1200 830 1L WHT SSA03

Item No: 0034018

SYLVANIA


PROTM



OPTICLIP R 1200 830 1L WHT SSA03 is a high efficacy low glare ceiling recessed mounted luminaire with replaceable light engines for office and education applications. White colour plastic optic (reflector + lens), direct light distribution. Luminaire dimensions: 1195x295x44mm. White body colour (RAL9016), IP40 (from the front), IK07, SylSmart Connected enabled with integrated sensor, 33.5W power consumption, 3000K (warm white) LED CCT, 4450lm luminous flux at 900mA drive current level, 131lm/W system efficacy, CRI>80, SDCM≤3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, luminance at 65° < 2000 cd/m2. Lifespan: 100,000 hours L80B20, photobiological safety risk group 0. Electrical protection Class II. Glow wire test 850°C.

Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Beam diameter [ft]	Beam diameter [in]
0.5	0.78	75.0°	0.78	2.56	25.6
1.0	1.56	75.0°	1.56	5.12	51.2
1.5	2.34	75.0°	2.34	7.68	76.8
2.0	3.12	75.0°	3.12	10.24	102.4
2.5	3.91	75.0°	3.91	12.80	128.0
3.0	4.69	75.0°	4.69	15.36	153.6
3.5	5.47	75.0°	5.47	17.92	179.2
4.0	6.25	75.0°	6.25	20.48	204.8
4.5	7.03	75.0°	7.03	23.04	230.4
5.0	7.81	75.0°	7.81	25.60	256.0
5.5	8.59	75.0°	8.59	28.16	281.6
6.0	9.37	75.0°	9.37	30.72	307.2
6.5	10.15	75.0°	10.15	33.28	332.8
7.0	10.93	75.0°	10.93	35.84	358.4
7.5	11.71	75.0°	11.71	38.40	384.0
8.0	12.49	75.0°	12.49	40.96	409.6
8.5	13.27	75.0°	13.27	43.52	435.2
9.0	14.05	75.0°	14.05	46.08	460.8
9.5	14.83	75.0°	14.83	48.64	486.4
10.0	15.61	75.0°	15.61	51.20	512.0
10.5	16.39	75.0°	16.39	53.76	537.6
11.0	17.17	75.0°	17.17	56.32	563.2
11.5	17.95	75.0°	17.95	58.88	588.8
12.0	18.73	75.0°	18.73	61.44	614.4
12.5	19.51	75.0°	19.51	64.00	640.0
13.0	20.29	75.0°	20.29	66.56	665.6
13.5	21.07	75.0°	21.07	69.12	691.2
14.0	21.85	75.0°	21.85	71.68	716.8
14.5	22.63	75.0°	22.63	74.24	742.4
15.0	23.41	75.0°	23.41	76.80	768.0
15.5	24.19	75.0°	24.19	79.36	793.6
16.0	24.97	75.0°	24.97	81.92	819.2
16.5	25.75	75.0°	25.75	84.48	844.8
17.0	26.53	75.0°	26.53	87.04	870.4
17.5	27.31	75.0°	27.31	89.60	896.0
18.0	28.09	75.0°	28.09	92.16	921.6
18.5	28.87	75.0°	28.87	94.72	947.2
19.0	29.65	75.0°	29.65	97.28	972.8
19.5	30.43	75.0°	30.43	99.84	998.4
20.0	31.21	75.0°	31.21	102.40	1024.0
20.5	31.99	75.0°	31.99	104.96	1049.6
21.0	32.77	75.0°	32.77	107.52	1075.2
21.5	33.55	75.0°	33.55	110.08	1100.8
22.0	34.33	75.0°	34.33	112.64	1126.4
22.5	35.11	75.0°	35.11	115.20	1152.0
23.0	35.89	75.0°	35.89	117.76	1177.6
23.5	36.67	75.0°	36.67	120.32	1203.2
24.0	37.45	75.0°	37.45	122.88	1228.8
24.5	38.23	75.0°	38.23	125.44	1254.4
25.0	39.01	75.0°	39.01	128.00	1280.0
25.5	39.79	75.0°	39.79	130.56	1305.6
26.0	40.57	75.0°	40.57	133.12	1331.2
26.5	41.35	75.0°	41.35	135.68	1356.8
27.0	42.13	75.0°	42.13	138.24	1382.4
27.5	42.91	75.0°	42.91	140.80	1408.0
28.0	43.69	75.0°	43.69	143.36	1433.6
28.5	44.47	75.0°	44.47	145.92	1459.2
29.0	45.25	75.0°	45.25	148.48	1484.8
29.5	46.03	75.0°	46.03	151.04	1510.4
30.0	46.81	75.0°	46.81	153.60	1536.0
30.5	47.59	75.0°	47.59	156.16	1561.6
31.0	48.37	75.0°	48.37	158.72	1587.2
31.5	49.15	75.0°	49.15	161.28	1612.8
32.0	49.93	75.0°	49.93	163.84	1638.4
32.5	50.71	75.0°	50.71	166.40	1664.0
33.0	51.49	75.0°	51.49	168.96	1689.6
33.5	52.27	75.0°	52.27	171.52	1715.2
34.0	53.05	75.0°	53.05	174.08	1740.8
34.5	53.83	75.0°	53.83	176.64	1766.4
35.0	54.61	75.0°	54.61	179.20	1792.0
35.5	55.39	75.0°	55.39	181.76	1817.6
36.0	56.17	75.0°	56.17	184.32	1843.2
36.5	56.95	75.0°	56.95	186.88	1868.8
37.0	57.73	75.0°	57.73	189.44	1894.4
37.5	58.51	75.0°	58.51	192.00	1920.0
38.0	59.29	75.0°	59.29	194.56	1945.6
38.5	60.07	75.0°	60.07	197.12	1971.2
39.0	60.85	75.0°	60.85	199.68	1996.8
39.5	61.63	75.0°	61.63	202.24	2022.4
40.0	62.41	75.0°	62.41	204.80	2048.0
40.5	63.19	75.0°	63.19	207.36	2073.6
41.0	63.97	75.0°	63.97	209.92	2099.2
41.5	64.75	75.0°	64.75	212.48	2124.8
42.0	65.53	75.0°	65.53	215.04	2150.4
42.5	66.31	75.0°	66.31	217.60	2176.0
43.0	67.09	75.0°	67.09	220.16	2201.6
43.5	67.87	75.0°	67.87	222.72	2227.2
44.0	68.65	75.0°	68.65	225.28	2252.8
44.5	69.43	75.0°	69.43	227.84	2278.4
45.0	70.21	75.0°	70.21	230.40	2304.0
45.5	70.99	75.0°	70.99	232.96	2329.6
46.0	71.77	75.0°	71.77	235.52	2355.2
46.5	72.55	75.0°	72.55	238.08	2380.8
47.0	73.33	75.0°	73.33	240.64	2406.4
47.5	74.11	75.0°	74.11	243.20	2432.0
48.0	74.89	75.0°	74.89	245.76	2457.6
48.5	75.67	75.0°	75.67	248.32	2483.2
49.0	76.45	75.0°	76.45	250.88	2508.8
49.5	77.23	75.0°	77.23	253.44	2534.4
50.0	78.01	75.0°	78.01	256.00	2560.0
50.5	78.79	75.0°	78.79	258.56	2585.6
51.0	79.57	75.0°	79.57	261.12	2611.2
51.5	80.35	75.0°	80.35	263.68	2636.8
52.0	81.13	75.0°	81.13	266.24	2662.4
52.5	81.91	75.0°	81.91	268.80	2688.0
53.0	82.69	75.0°	82.69	271.36	2713.6
53.5	83.47	75.0°	83.47	273.92	2739.2
54.0	84.25	75.0°	84.25	276.48	2764.8
54.5	85.03	75.0°	85.03	279.04	2790.4
55.0	85.81	75.0°	85.81	281.60	2816.0
55.5	86.59	75.0°	86.59	284.16	2841.6
56.0	87.37	75.0°	87.37	286.72	2867.2
56.5	88.15	75.0°	88.15	289.28	2892.8
57.0	88.93	75.0°	88.93	291.84	2918.4
57.5	89.71	75.0°	89.71	294.40	2944.0
58.0	90.49	75.0°	90.49	296.96	2969.6
58.5	91.27	75.0°	91.27	299.52	2995.2
59.0	92.05	75.0°	92.05	302.08	3020.8
59.5	92.83	75.0°	92.83	304.64	3046.4
60.0	93.61	75.0°	93.61	307.20	3072.0
60.5	94.39	75.0°	94.39	309.76	3097.6
61.0	95.17	75.0°	95.17	312.32	3123.2
61.5	95.95	75.0°	95.95	314.88	3148.8
62.0	96.73	75.0°	96.73	317.44	3174.4
62.5	97.51	75.0°	97.51	320.00	3200.0
63.0	98.29	75.0°	98.29	322.56	3225.6
63.5	99.07	75.0°	99.07	325.12	3251.2
64.0	99.85	75.0°	99.85	327.68	3276.8
64.5	100.63	75.0°	100.63	330.24	3302.4
65.0	101.41	75.0°	101.41	332.80	3328.0
65.5	102.19	75.0°	102.19	335.36	3353.6
66.0	102.97	75.0°	102.97	337.92	3379.2
66.5	103.75	75.0°	103.75	340.48	3404.8
67.0	104.53	75.0°	104.53	343.04	3430.4
67.5	105.31	75.0°	105.31	345.60	3456.0
68.0	106.09	75.0°	106.09	348.16	3481.6
68.5	106.87	75.0°	106.87	350.72	3507.2
69.0	107.65	75.0°	107.65	353.28	3532.8
69.5	108.43	75.0°	108.43	355.84	3558.4
70.0	109.21	75.0°	109.21	358.40	3584.0
70.5	110.00	75.0°	110.00	360.96	3609.6
71.0	110.78	75.0°	110.78	363.52	3635.2
71.5	111.56	75.0°	111.56	366.08	3660.8
72.0	112.34	75.0°	112.34	368.64	3686.4
72.5	113.12	75.0°	113.12	371.20	3712.0
73.0	113.90	75.0°	113.90	373.76	3737.6
73.5	114.68	75.0°	114.68	376.32	3763.2
74.0	115.46	75.0°	115.46	378.88	3788.8
74.5	116.24	75.0°	116.24	381.44	3814.4
75.0	117.02	75.0°	117.02	384.00	3840.0
75.5	117.80	75.0°	117.80	386.56	3865.6
76.0	118.58	75.0°	118.58	389.12	3891.2
76.5	119.36	75.0°	119.36	391.68	3916.8
77.0	120.14	75.0°	120.14	394.24	3942.4
77.5	120.92	75.0°	120.92	396.80	3968.0
78.0	121.70	75.0°	121.70	399.36	3993.6
78.5	122.48	75.0°	122.48	401.92	4019.2
79.0	123.26	75.0°	123.26	404.48	4044.8
79.5	124.04	75.0°	124.04	407.04	4070.4
80.0	124.82	75.0°	124.82	409.60	4096.0
80.5	125.60	75.0°	125.60	412.16	4121.6
81.0	126.38	75.0°	126.38	414.72	4147.2
81.5	127.16	75.0°	127.16	417.28	4172.8
82.0	127.94	75.0°	127.94	419.84	4198.4
82.5	128.72	75.0°	128.72	422.40	4224.0
83.0	129.50	75.0°	129.50	424.96	4249.6
83.5	130.28	75.0°	130.28	427.52	4275.2
84.0	131.06	75.0°	131.06	430.08	4300.8
84.5	131.84	75.0°	131.84	432.64	4326.4
85.0	132.62	75.0°	132.62	435.20	4352.0
85.5	133.40	75.0°	133.40	437.76	4377.6
86.0	134.18	75.0°	134.18	440.32	4403.2
86.5	134.96	75.0°	134.96	442.88	4428.8
87.0	135.74	75.0°	135.74	445.44	4454.4
87.5	136.52	75.0°	136.52	448.00	4480.0
88.0	137.30	75.0°	137.30	450.56	4505.6
88.5	138.08	75.0°	138.08	453.12	4531.2
89.0	138.86	75.0°	138.86	455.68	4556.8
89.5	139.64	75.0°	139.64	458.24	4582.4
90.0	140.42	75.0°	140.42	460.80	4608.0
90.5	141.20	75.0°	141.20	463.36	4633.6
91.0	141.98	75.0°	141.98	465.92	4659.2
91.5	142.76	75.0°	142.76	468.48	4684.8
92.0	143.54	75.0°	143.54	471.04	4710.4
92.5	144.32	75.0°	144.32	473.60	4736.0
93.0	145.10	75.0°	145.10	476.16	4761.6
93.5	145.88	75.0°	145.88	478.72	4787.2
94.0	146.66	75.0°	146.66	481.28	4812.8
94.5	147.44	75.0°	147.44	483.84	4838.4
95.0	148.22	75.0°	148.22		

OPTICLIP R 1200 830 1L WHT SSA03

Item No: 0034018

SYLVANIA

General data

Product name	OPTICLIP R 1200 830 1L WHT SSA03
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Built in presence detector	PIR
General application	Office, Education
Operating temperature range (°C)	5°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
E-number FI	4170631
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4450
Luminaire efficacy (lm/W)	133
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	75
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Electrical data

Emergency type	
Total power consumption (W)	33.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Connected (SSA)
Minimum dimming level (%)	1
Drive current (mA)	900
Max. drive current (mA)	900
Drive current - Range (mA)	/ 900mA
Inrush Current (A)	15
Inrush Duration (µs)	220
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	27
Max. products per 16A C Breaker	33
Max. products per 20A C Breaker	42
Max. products per 10A B Breaker	12
Max. products per 13A B Breaker	16
Max. products per 16A B Breaker	20
Max. products per 20A B Breaker	25
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	1.5

OPTICLIP R 1200 830 1L WHT SSA03

Item No: 0034018

SYLVANIA

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B20	50000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Reflector finish	Matt
Nominal Product Length (mm)	1195
Nominal Product Width (mm)	295
Nominal Product Height (mm)	44
Weight (kg)	3.5

Packaging

Product EAN number	5410288340180
Packaging single length / height (cm)	124.5
Packaging single width (cm)	6.5
Packaging single depth (cm)	32.0
DUN14 (inner)	05410288340180
Units per outer package	1
Packaging outer length / height (cm)	124.5
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	32.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-25
Dry applications use only	No