

Granit IP65 DALI 26000lm 865 WB

Item No: 0039625


SYLVANIA



Integrated LED highbay; Black aluminium housing; 25500 Lm; 185 W; 137 Lm/W; 6500K; Drive current: 3200mA; CRI 80; 85° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 385 x 194 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.85	Ø171 Ø171	7212 1666
1.0	1.69	Ø342 Ø342	1803 416
1.5	2.54	Ø513 Ø513	827 184
2.0	3.38	Ø684 Ø684	464 107
2.5	4.23	Ø855 Ø855	292 66
3.0	5.07	Ø1026 Ø1026	204 46

Distance [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Half beam angle: 80.4°)



Granit IP65 DALI 26000lm 865 WB

Item No: 0039625

SYLVANIA

General data

Product name	Granit IP65 DALI 26000lm 865 WB
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
E-number FI	4357022
Warranty	5 years

Optical data

Fixture luminous flux (lm)	25500
Luminaire efficacy (lm/W)	137
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	185
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	3200
Inrush Current (A)	92
Inrush Duration (µs)	224
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	6
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	9
Max. products per 20A C Breaker	12
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	7

Lifetime data

Lifespan L80 B50	90000
Lifespan L80 B20	70000
Lifespan L80 B10	65000
Lifespan L90 B50	45000

Granit IP65 DALI 26000lm 865 WB

Item No: 0039625

SYLVANIA

Physical data

Housing colour	Black
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	385
Nominal Product Width (mm)	385
Nominal Product Height (mm)	194
Nominal Product Diameter (mm)	385
Weight (kg)	4.33

Packaging

Product EAN number	5410288396255
Packaging single length / height (cm)	44.5
Packaging single width (cm)	44.5
Packaging single depth (cm)	19.5
DUN14 (inner)	05410288396255
Units per outer package	1
Packaging outer length / height (cm)	44.5
Packaging outer width (cm)	44.5
Packaging outer depth (cm)	19.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-30-50