

OTAO LINEAR ST EMPRO MODULE WH

Item No: 0041822

SYLVANIA

General data

Product name	OTAO LINEAR ST EMPRO MODULE WH
Technology	Emergency Pack
Type of accessory	Other
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
Built in presence detector	NONE
General application	Education, Office
Operating temperature range (°C)	5°C...+40°C
ETIM Class	EC000471
Warranty	5 years

Optical data

Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Luminous flux (emergency) (lm)	350

Electrical data

Emergency type	
Emergency duration (h)	3
Electrical protection	Class I
Max. products per 10A C Breaker	100
Max. products per 16A C Breaker	100
Max. products per 16A B Breaker	100

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Nominal Product Length (mm)	170
Nominal Product Width (mm)	50
Nominal Product Height (mm)	73
Weight (kg)	0.45

Packaging

Product EAN number	5410288418223
Packaging single length / height (cm)	32.0
Packaging single width (cm)	6.1
Packaging single depth (cm)	7.8
DUN14 (inner)	15410288418220
Units per outer package	5
Packaging outer length / height (cm)	34.0
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	37.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-40