


PANEL IP66 CR R 623S MSG L3 5360LM 840

Item No: 0042761

SYLVANIA

LiteGuard™



PANEL IP66 CR R 623S MSG L3 5360LM 840 is a recessed LED lighting fixture designed for clean areas in hospitals, laboratories, microelectronics production, food industry, clean screwless design for easy cleaning with rounded edges of the frame eliminates the sediments and bacteriums creation, powder coated steel body with white finishing (RAL9016), diffuser made of matt tempered safety glass, 623x623x79mm luminaire dimensions, 5360lm luminous flux, 37W system power, 145lm/W efficacy, CRI Ra>80 4000K CCT light source, suitable for ambient temperatures from -20°C up to 60°C, lifespan: L80B10 70000h @Ta 30°C, L70B10 100000hr @ Ta 30°C, certified for clean areas in compliance with ISO 14644-1 class 2-9, minimum height of mounting space is 200 mm, electrical connection by means of ADELS connector, maximum cross section of wires 2,5 mm², impact protection IK08, ingress protection rating IP66/IP50 upper side of the luminaire, electrical protection Class I, non-dimmable constant current driver, 5 years warranty.

PANEL IP66 CR R 623S MSG L3 5360LM 840

Item No: 0042761

SYLVANIA


Technical Assets

Photometrics

0.5	1.13 1.12	E(1°) E(C90) E(C0)	8902 1291 1211
1.0	2.27 2.24	E(1°) E(C90) E(C0)	2225 323 325
1.5	3.40 3.37	E(1°) E(C90) E(C0)	989 143 145
2.0	4.54 4.49	E(1°) E(C90) E(C0)	599 81 82
2.5	5.67 5.61	E(1°) E(C90) E(C0)	399 52 52
3.0	6.81 6.73	E(1°) E(C90) E(C0)	247 38 38

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (half beam angle: 96.6°)
— C90 - C270 (half beam angle: 97.2°)



General data

Product name	PANEL IP66 CR R 623S MSG L3 5360LM 840
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+60°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	5360
Luminaire efficacy (lm/W)	145
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG0

PANEL IP66 CR R 623S MSG L3 5360LM 840

Item No: 0042761

SYLVANIA

Electrical data

Emergency type	
Total power consumption (W)	37
Primary Supply/Product voltage - min (V)	240.0
Primary Supply/Product voltage - max (V)	220.0
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Inrush Current (A)	23
Inrush Duration (µs)	140
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	39
Max. products per 16A C Breaker	64
Max. products per 16A B Breaker	38
Connectable conductor cross section - Min (mm²)	0.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	100000
------------------	--------

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP66
IK rating	IK08
Diffuser finish	Opal
Diffuser material	Safety tempered glass
Nominal Product Length (mm)	623
Nominal Product Width (mm)	623
Nominal Product Height (mm)	79
Weight (kg)	12.0

Packaging

Product EAN number	5410288427614
Packaging single length / height (cm)	65.0
Packaging single width (cm)	65.0
Packaging single depth (cm)	9.5
DUN14 (inner)	05410288427614
Units per outer package	1
Packaging outer length / height (cm)	65.0
Packaging outer width (cm)	65.0
Packaging outer depth (cm)	9.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-60