


Muro Surface IP65 1700-3250lm 840 PH Grey

Item No: 0049944

SYLVANIA


PRO




Muro Surface is a wall mounted fixture for exterior lighting applications. Comes with aluminium housing in RAL7016 anthracite grey colour, frosted PC diffuser, IP65, IK10, Class I, 4000K, non-dimmable multipower driver with 5 settings, 1700 / 1900 / 2750 / 3150 / 3250 lm, 14 / 16 / 24 / 27 / 28 W, up to 121 lm/W total system efficacy, switchable built in Mini photocell, CRI80, Asymmetrical beam, 119.000 hrs L70B50 lifespan, 304 x 305 x 155 mm (L x W x D) dimensions, 4.1 kg weight.

Technical Assets

Dimensions (mm)



Photometrics



Muro Surface IP65 1700-3250lm 840 PH Grey

Item No: 0049944

SYLVANIA

General data

Product name	Muro Surface IP65 1700-3250lm 840 PH Grey
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
Built in presence detector	NONE
General application	Hospitality, Logistics & Industry, Museums & Galleries, Office
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3250
Luminaire efficacy (lm/W)	116
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Asymmetric
Photobiological Risk Group	RG1

Electrical data

Emergency type	
Total power consumption (W)	28
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	700
Inrush Current (A)	5
Inrush Duration (µs)	50
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	30
Max. products per 13A C Breaker	40
Max. products per 16A C Breaker	50
Max. products per 20A C Breaker	60
Max. products per 10A B Breaker	30
Max. products per 13A B Breaker	40
Max. products per 16A B Breaker	50
Max. products per 20A B Breaker	60
Connectable conductor cross section - Min (mm²)	1
Connectable conductor cross section - Max (mm²)	2.5

Muro Surface IP65 1700-3250lm 840 PH Grey

Item No: 0049944



Lifetime data

Lifespan L70 B50	119000
Lifespan L70 B20	113000
Lifespan L70 B10	110000
Lifespan L80 B50	76000
Lifespan L80 B20	72000
Lifespan L80 B10	70000
Lifespan L90 B50	37000
Lifespan L90 B20	35000
Lifespan L90 B10	34000

Physical data

Housing colour	RAL 7016 - Anthracite
IP rating	IP65
IK rating	IK10
Diffuser finish	Other
Diffuser material	None
Reflector finish	Not Applicable
Nominal Product Length (mm)	304
Nominal Product Width (mm)	155
Nominal Product Height (mm)	305
Weight (kg)	4.1

Packaging

Product EAN number	5410288499444
Packaging single length / height (cm)	31.5
Packaging single width (cm)	31.0
Packaging single depth (cm)	16.5
DUN14 (inner)	15410288499441
Units per outer package	2
Packaging outer length / height (cm)	63.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	18.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-45