

Start Flood IP65 1000LM 840 Black

Item No: 0050161

SYLVANIA


START



The streamlined, durable, lightweight die-cast aluminium body makes Start Flood IP65 a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 1000 lm, 9.5 W, 105 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 100 x 108 x 23 mm (L x W x H). Weight: 0.26 kg.


Technical Assets

Dimensions (mm)



Photometrics

Distance (m)	Cone diameter (m)	Beam angle (°)	Beam diameter (m)	Illuminance (lx)
0.5	1.46 1.15	50° 40°	1.46 1.15	1571 142
1.0	2.92 2.30	50° 40°	2.92 2.30	390 38
1.5	4.38 3.44	50° 40°	4.38 3.44	175 16
2.0	5.84 4.60	50° 40°	5.84 4.60	96 14
2.5	7.30 5.75	50° 40°	7.30 5.75	63 9
3.0	8.76 6.90	50° 40°	8.76 6.90	44 8



Start Flood IP65 1000LM 840 Black

Item No: 0050161

SYLVANIA

General data

Product name	Start Flood IP65 1000LM 840 Black
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted, Ceiling surface mounting
Built in presence detector	NONE
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC001744
E-number FI	4579626
Warranty	3 years

Optical data

Fixture luminous flux (lm)	1000
Luminaire efficacy (lm/W)	105
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	110
Distribution type	Symmetric
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	9.5
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear type	Not required
No. Of switching cycles before premature failures	>15000
Dimmable	No
Dimming method	N/A
Drive current (mA)	41
Inrush Current (A)	1
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	132
Max. products per 13A C Breaker	172
Max. products per 16A C Breaker	216
Max. products per 20A C Breaker	264
Max. products per 10A B Breaker	80
Max. products per 13A B Breaker	103
Max. products per 16A B Breaker	127
Max. products per 20A B Breaker	159
Connectable conductor cross section - Min (mm²)	1
Connectable conductor cross section - Max (mm²)	1

Lifetime data

Lifespan L70 B50	90000
Lifespan L80 B50	73000
Lifespan L80 B20	64000

Start Flood IP65 1000LM 840 Black

Item No: 0050161



Physical data

Housing colour	Black
IP rating	IP65
IK rating	IK06
Diffuser finish	Transparent
Diffuser material	Glass
Reflector finish	Not Applicable
Nominal Product Length (mm)	100
Nominal Product Width (mm)	108
Nominal Product Height (mm)	23
Weight (kg)	0.26

Packaging

Product EAN number	5410288501611
Packaging single length / height (cm)	13.0
Packaging single width (cm)	5.5
Packaging single depth (cm)	15.5
DUN14 (inner)	15410288501618
Units per outer package	6
Packaging outer length / height (cm)	36.0
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	17.5

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40